



**T.C. Ticaret Bakanlığı**  
**İthalat Genel Müdürlüğü**

Değerli Sanayicilerimiz;

Bilindiği üzere, sanayicimizin ihtiyaç duyduğu hammadde ve yarı mamul niteliğindeki sanayi ürünlerine ilişkin olarak üretimi olmayan ürünlerde gümrük vergilerinin askıya alınması, üretimi tüketimi karşılamayan ürünlerde ise tarife kontenjanı açılmasına ilişkin başvurular, ülkemiz temsilcilerinin de katıldığı toplantılarda Avrupa Komisyonu ile müzakere edilerek karara bağlanmakta ve düzenlemeler her yıl 1 Ocak ve 1 Temmuz tarihlerinde yürürlüğe girmektedir.

Bu çerçevede, Avrupa Birliği (AB) ya da Türk firmalarınca 01/07/2026 tarihinden itibaren gümrük vergilerinin askıya alınması veya tarife kontenjanı uygulanması ya da mevcut gümrük vergisi indirimlerinin kaldırılması talep edilen eşyaya ilişkin liste Ek-1’de, hali hazırda gümrük vergileri askıya alınmış olan eşyaya ilişkin liste Ek-2’de, AB tarafından tarife kontenjanı açılmış olan eşyaya ilişkin liste Ek-3’te, ülkemiz tarafından tarife kontenjanı açılmış olan eşyaya ilişkin liste ise Ek-4’te yer almaktadır.

Bu itibarla; üretici firmalarımızın Ek-1’de yer alan gümrük vergilerinin askıya alınmasına ilişkin taleplere dair itirazlarını, eş başvuru taleplerini ya da bu listede bulunan itiraz başvurularına ilişkin mevcut askıya almaların yürürlükte kalmasına dair taleplerini **5 Aralık 2025** tarihine kadar; Ek-2, Ek-3 ve Ek-4’te yer alan eşyada hali hazırda uygulanan indirimli gümrük vergisi uygulamalarının sonlandırılmasına ilişkin taleplerini ise **6 Kasım 2025** tarihine kadar resmi yazı ile Ticaret Bakanlığı İthalat Genel Müdürlüğüne iletmeleri gerekmektedir.

Başvuruların en son belirtilen tarihlere kadar tam ve eksiksiz olarak firmaların Kayıtlı Elektronik Posta (KEP) adreslerinden Ticaret Bakanlığı KEP adresine (ticaretbakanligi@hs01.kep.tr) elektronik ortamda iletilmesi gerekmektedir.

Başvurulara ilişkin detaylı bilgi ve formlara <https://www.ticaret.gov.tr/ithalat/askiya-alma-ve-tarife-kontenjan/askiya-alma-sistemi> adresinden ulaşılabilir.

Bilgileri ile konunun önemine binaen üyeniz firmalara eksiksiz olarak duyurulması hususunda gereğini rica ederim.

Not: Askıya alma sistemine ilişkin detaylı bilgi için 2025/18 sayılı Askıya Alma Sistemine İlişkin Tebliğ (İthalat: 2025/18) incelenebilir. Ayrıca; listede yer alan ürünlerin özel tanımlı olmasından dolayı, firmalar tarafından GTP’den ziyade ürün tanımlarının incelenmesi gerekmektedir.

Müge DAĞLI  
Bakan a.  
Daire Başkanı

Murat ALBAYRAK  
Bakan a.  
Daire Başkanı V.

Sinan YANAZ  
Bakan a.  
Daire Başkanı

## İlgili Kişilerin İletişim Bilgileri:

### Kimyasallar ve Tekstil Hammaddeleri:

- Özge SEZGİN	Uzman	T: 0 312 204 99 25	E: sezgino@ticaret.gov.tr
- Furkan Eren KAHVECİ	Uzman	T: 0 312 204 95 77	E: kahvecif@ticaret.gov.tr
- Ekin Deniz GÖÇÜK	Uzman	T: 0 312 204 95 70	E: timured@ticaret.gov.tr
- Mehmet BARAN	Uzman	T: 0 312 204 95 81	E: m.baran2@ticaret.gov.tr
- Serdar AKÇAY	Uzman	T: 0 312 204 98 83	E: s.akcay2@ticaret.gov.tr
- Ali YANAR	Uzman Yardımcısı	T: 0 312 204 99 74	E: a.yanar3@ticaret.gov.tr
- Furkan DEMİRCİ	Uzman Yardımcısı	T: 0 312 204 92 93	E: f.demirci5@ticaret.gov.tr

### Maden Metal ve Nakil Vasıtaları:

- Sude GÜRCAN	Uzman	T: 0 312 204 94 92	E: gurcans@ticaret.gov.tr
- Elif Tuğçe KANAK	Uzman	T: 0 312 204 94 90	E: e.katircioglu@ticaret.gov.tr
- Öznur ÖNAL	Uzman	T: 0 312 204 91 89	E: o.onal4@ticaret.gov.tr
- Fatma Hilal YÜNEY	Uzman Yardımcısı	T: 0 312 204 92 96	E: yuneyf@ticaret.gov.tr

### Makine, Elektrik ve Elektronik:

- Tuğba Köse SANDALCI	Uzman	T: 0 312 204 99 30	E: sandalcit@ticaret.gov.tr
- Ceren Koç PEKTEZEL	Uzman Yardımcısı	T: 0 312 204 96 68	E: c.kocpektezel@ticaret.gov.tr
- Bilgenur ÜÇGÜL	Uzman Yardımcısı	T: 0 312 204 99 66	E: b.ucgul@ticaret.gov.tr
- Gamze ÖZGÜN	Uzman Yardımcısı	T: 0 312 204 87 60	E: g.ozgun@ticaret.gov.tr

## **CYCLE 2026-07**

Sorting order:

A – first 'quotas', then 'suspensions'

B – **new** requests, **amending** requests.

>>>The duty suspension and quota requests on the following list are currently under discussion. The data available on this list may not represent the final state of the discussions within the relevant Commission Working group.

Please note that it cannot be guaranteed that the information available exactly reproduces an officially adopted text. Only European Union legislation published in the Official Journal of the European Union is deemed authentic<<<<

<b>CN code</b>	<b>TARIC</b>	<b>Reference Mail</b>	<b>Description</b>	<b>Quotas</b>	<b>New or amendment request</b>	<b>Measure status</b>	<b>Partner Position Country</b>	<b>Partner Position</b>	<b>Public Comments</b>
2909 49 80		8823392/2025	3-Methoxy-3-methyl-1-butanol (CAS RN 56539-66-3); purity by weight 99 % or more	Q/50000kilograms, 01.07-31.12	<b>New</b>	UNDER EXAMINATION	TR	Applicant	Round 2026.07 Surface Cleaners and Liquid Laundry Detergent
2924 19 00		8426547/2025	ADMA 10: N,N-Dimethylcapramide (CAS RN 14433-76-2) with a purity by weight of 95 % or more	Q/2000tonnes, 01.07-31.12	<b>New</b>	UNDER EXAMINATION	BE	Applicant	Round 2026.07 quota request for solvent or co-solvent used for formulating plant protection products (fungicide)
2929 10 00		8738626/2025	Methylene diphenyl diisocyanate (CAS RN 101-68-8); purity by weight 99 % or more	Q/65000kilograms, 01.07-31.12	<b>New</b>	UNDER EXAMINATION	TR	Applicant	Round 2026.07 Elastane for yarn production
2933 39 99		8426856/2025	Fluopyram (ISO) (CAS RN 658066-35-4) with a purity by weight of 96 % or more	Q/75tonnes, 01.07-31.12	<b>New</b>	UNDER EXAMINATION	FR	Applicant	Round 2026.07 Fluopyram, a fungicide used in agriculture
3920 10 89		8426798/2025	Transparent polyolefin elastomer (POE) film: • thickness of not less than 0.44 mm and not more than 0.46 mm, • width of not less than 100 cm and not more than	Q/33tonnes, 01.07-31.12	<b>New</b>	UNDER EXAMINATION	SI	Applicant	Round 2026.07 Transparent polyolefin elastomer (POE) film for protecting

			140 cm, • basis weight of not less than 360 g/m <sup>2</sup> and not more than 400 g/m <sup>2</sup> , • lamination shrinkage of up to 3 % in the machine direction and up to 1.5 % in the transverse direction, • volume resistivity greater than $1.0 \times 10^{15} \Omega\text{-cm}$ , • adhesion to glass greater than 60 N/cm, and • light transmittance above 90 % in the wavelength range of 380 - 1100 nm, for use in the production of photovoltaic cells or modules as the front protective (encapsulation) layer.						photovoltaic modules from external influences
ex 2917 13 90	10	1069948/2012 1151/2007	DE 15.9.2025 new text description: Dimethyl sebacate (CAS RN 106-79-6) with a purity by weight of 97 % or more ----- Dimethyl sebacate (CAS RN 106-79-6)	Q/1000tonnes, 01.07-30.06	<b>Amendment</b>	UNDER EXAMINATION	DE IT	Applicant Applicant	Round 2026/07 request for amendment ROUND 2013-07-01: used as intermediate for the production of additives for plastic (light stabilizers) -running quota - 09.2769, 1151/2007, 2917 13 90 10 could be transfered into the Suspension Regulation
ex 2923 90 00	88	1956962/2022	Aqueous solution containing by weight 78 % or more but not more than 82 % of [2-(acryloyloxy)ethyl]trimethylammonium chloride (CAS RN 44992-01-0)	Q/10000tonnes, 01.07-31.12	<b>Amendment</b>	UNDER EXAMINATION	FR	Applicant	Round 2026/01 request for quota increase Round 2023-01 used in the manufacturer of polymers intended for water treatment
ex 8409 91 00	15	6838521/2024	SE 15.09.2025 Proposed new description Cylinder head blank for a four cylinder engine with 10 cores, made of aluminium alloy EN AC-45500, with: - no other components, - a hardness of 90HB or more, - casting defects size of not more than 0,4 mm and not more than 10 defects per cm <sup>2</sup> ,	Q/20000pieces, 01.07-30.06	<b>Amendment</b>	UNDER EXAMINATION	SE	Applicant	Round 2026.07 amendment request Round 2025/7 used in the manufacture of spark-ignition internal combustion engines for vehicles of tariff heading 8703

			<ul style="list-style-type: none"> <li>- a dendrite arm space in combustion chamber of not more than 25 µm,</li> <li>- a double deck water jacket design,</li> <li>- a weight of 14 kg or more but not more than 19 kg,</li> <li>- a length of 460 mm or more but not more than 510 mm,</li> <li>- a height of 260 mm or more but not more than 286 mm and</li> <li>- a width of 140 mm or more but not more than 150 mm</li> </ul> <p>-----</p> <p>Cylinder head blank for a four cylinder engine with 10 cores, made of aluminium alloy EN AC-45500, with:</p> <ul style="list-style-type: none"> <li>- no other components,</li> <li>- a hardness of 52 HRB or more,</li> <li>- casting defects size of not more than 0,4 mm and not more than 10 defects per cm<sup>2</sup>,</li> <li>- a dendrite arm space in combustion chamber of not more than 25 µm,</li> <li>- a double deck water jacket design,</li> <li>- a weight of 14 kg or more but not more than 19 kg,</li> <li>- a length of 506 mm or more but not more than 510 mm,</li> <li>- a height of 282 mm or more but not more than 286 mm and</li> <li>- a width of 143,7 mm or more but not more than 144,3 mm</li> </ul>						
ex 8714 91 10 ex 8714 91 10 ex 8714 91 10	21 31 75	1095094/2012	Bicycle frame, constructed from carbon fibres and artificial resin, for use in the manufacture of bicycles (including electric bicycles) (1)	Q/600000pieces, 01.07-31.12	<b>Amendment</b>	UNDER EXAMINATION	AT EU FR IT NL PT	Applicant Applicant Applicant Applicant Applicant	Round 2026.07 amendment request ROUND 2013-07-01: A bicycle frame is the supporting construction of the bike. This part connects all the parts of the bike together

CN code	TARIC	Reference Mail	Description	<u>Suspensions</u>	New or New request	Measure status	Partner Position Country	Partner Position	Public Comments
1515 60 99		8933399/2025	Microbial oil, refined or semi-refined, but not chemically modified, containing 35 % by weight or more but not exceeding 70 % by weight of esterified arachidonic acid and not more than 3 % by weight of esterified docosahexaenoic acid in triglycerides	<u>S</u>	New	UNDER EXAMINATION	DE	Applicant	Round 2026.7 to manufacture nutritional products
2836 91 00		8739368/2025	Lithium carbonate, battery grade	<u>S</u>	New	UNDER EXAMINATION	BE	Applicant	Round 2026.07 Battery grade lithium carbonate
2904 99 00		8329465/2025	Trifluoromethanesulfonic acid (CAS RN 1493-13-6) with a purity by weight of 99 % or more	<u>S</u>	New	UNDER EXAMINATION	DE	Applicant	Round 2026/07 for use in chemical and pharmaceutical industry
2921 43 00		8329511/2025	2-Aminobenzotrifluoride (CAS RN 88-17-5) with a purity by weight of 98 % or more	<u>S</u>	New	UNDER EXAMINATION	DE	Applicant	Round 2026/07 for use in the manufacture of pigments
2922 29 00		8176820/2025	m-Anisidine (CAS RN 536-90-3) with a purity by weight of 95 % or more	<u>S</u>	New	UNDER EXAMINATION	CZ	Applicant	Round 2026/07 - used in the production of dyes
2924 19 00		8160472/2025	4-(2,2-diethoxyacetyl)-3,5-difluoro-N-methylbenzamide (CAS RN 3089027-90-4) with a purity by weight of 95 % or more	<u>S</u>	New	UNDER EXAMINATION	AT	Applicant	Round 2026/07 for use in the pharmaceutical industry
2930 90 95		8117136/2025	4,4,5,5,5-Pentafluoropentyl carbamimidothioate, methanesulfonate (CAS RN 1107606-68-7), with a purity by weight of 99 % or more	<u>S</u>	New	UNDER EXAMINATION	IT	Applicant	Round 2026/07 for use in the pharmaceutical industry
2930 90 95		8160422/2025	Trimethyl(oxo)-λ <sup>6</sup> -sulfanylium chloride (CAS RN 5034-06-0) with a purity by weight of 98 % or more	<u>S</u>	New	UNDER EXAMINATION	AT	Applicant	Round 2026/07 for use in pharmaceutical industry
2931 90 00		8116955/2025	(2-Fluoro-4-phenoxyphenyl)boronic acid (CAS	<u>S</u>	New	UNDER	IT	Applicant	Round 2026/07 for use

			RN 1414356-30-1), with a purity by weight of 99 % or more			EXAMINATION			in the pharmaceutical industry
2932 19 00		8160510/2025	(2,2-Diphenyltetrahydrofuran-3-yl)methanol (CAS RN 93651-75-3) with a purity by weight of 98 % or more	<u>S</u>	New	UNDER EXAMINATION	AT	Applicant	Round 2026/07 for use in the pharmaceutical industry
2933 19 90		8176713/2025	m-(4,5-Dihydro-3-methyl-5-oxo-1H-pyrazol-1-yl) benzenesulphonic acid (CAS RN 119-17-5) with a purity by weight of 95 % or more	<u>S</u>	New	UNDER EXAMINATION	CZ	Applicant	Round 2026/07 for use in the production of pigments
2933 19 90		8867025/2025	Isomeric mixture of 2-(3,4-dimethyl-1H-pyrazol-1-yl)succinic acid and 2-(4,5-dimethyl-1H-pyrazol-1-yl)succinic acid (CAS RN 2241455-89-8) with a purity of 97 % by weight or more	<u>S</u>	New	UNDER EXAMINATION	DE	Applicant	Round 2026/07 for use in the production of fertilizers
2933 39 99		8160326/2025	Ethyl hydrazinoacetate hydrochloride (CAS RN 6945-92-2) with a purity by weight of 98 % or more	<u>S</u>	New	UNDER EXAMINATION	ES	Applicant	Round 2026/01 for use in the pharmaceutical industry
2933 39 99		8160098/2025	5-chloro-1-(4-piperidyl)-1H-benzimidazol-2(3H)-one (CAS RN 53786-28-0) with a purity by weight of 99 % or more	<u>S</u>	New	UNDER EXAMINATION	ES	Applicant	Round 2026/07 for use in the pharmaceutical industry
2933 39 99		8242168/2025	Cyantranilprole (CAS RN 736994-63-1) with a purity by weight of 90 % or more	<u>S</u>	New	UNDER EXAMINATION	DE	Applicant	Round 2026/07 used in the manufacture of insecticides
2933 59 95		7874250/2025	3-iodo-1H-pyrazolo[3,4-d] pyrimidin-4-amine (CAS RN 151266-23-8), with a purity by weight of 98 % or more	<u>S</u>	New	UNDER EXAMINATION	IT	Applicant	Round 2026/07 for use in the pharmaceutical industry
2933 59 95		8246089/2025	Pirimiphos-methyl (ISO)(CAS RN 29232-93-7) with a purity by weight of 91 % or more	<u>S</u>	New	UNDER EXAMINATION	DE	Applicant	Round 2026/07 used in the manufacture of insecticides
2933 69 80		8242060/2025	Tris([1,1'-biphenyl]-4-yl)-1,3,5-triazine (CAS RN 31274-51-8) with a purity by weight of 97 % or more	<u>S</u>	New	UNDER EXAMINATION	DE	Applicant	Round 2026/07 used in the manufacture of sun creams

2933 99 80		8160198/2025	1-(3-chloropropyl)-1,3-dihydro-2H-benzimidazol-2-one (CAS RN 62780-89-6) with a purity by weight of 97 % or more	<u>S</u>	New	UNDER EXAMINATION	ES	Applicant	Round 2026/01 for use in pharmaceutical industry
2933 99 80		7871687/2025	Allyl (2S,4S)-4-benzoylsulfanyl-2-(dimethylcarbamoyl)pyrrolidine-1-carboxylate (CAS RN 141818-73-7) with a purity by weight of 96 % or more	<u>S</u>	New	UNDER EXAMINATION	IT	Applicant	Round 2026.7 for the pharmaceutical industry
2934 99 90		7873550/2025	(6R,7R)-Benzhydryl 3-hydroxy-8-oxo-7-(2-phenylacetamido)-5-thia-1-azabicyclo [4.2.0] oct-2-ene-2-carboxylate (CAS RN 54639-48-4) with a purity by weight of 95 % or more	<u>S</u>	New	UNDER EXAMINATION	IT	Applicant	Round 2026/07 for use in the pharmaceutical industry
2934 99 90		8117043/2025	Benzyl-4-(oxetan-3-yl) piperazine-1-carboxylate (CAS RN 1254115-22-4), with a purity by weight of 99 % or more	<u>S</u>	New	UNDER EXAMINATION	IT	Applicant	Round 2026/07 for use in the pharmaceutical industry
2934 99 90		8117362/2025	Adenosine 5'-(trihydrogen diphosphate), 2'-(dihydrogen phosphate), 5',5'-ester with 3-(aminocarbonyl)-1-β-d-ribofuranosylpyridinium hydroxide, inner salt, disodium salt (CAS RN 24292-60-2), with a purity by weight of 97 % or more	<u>S</u>	New	UNDER EXAMINATION	IT	Applicant	Round 2026/07 for use in the pharmaceutical industry
2934 99 90		7870099/2025	(6R-trans)-7-Amino-8-oxo-3-[[[1,2,5,6-tetrahydro-2-methyl-5,6-dioxo-1,2,4-triazin-3-yl]thio]methyl]-5-thia-1-azabicyclo[4.2.0]oct-2-ene-2-carboxylic acid (CAS RN 58909-56-1) with a purity by weight of 97 % or more	<u>S</u>	New	UNDER EXAMINATION	IT	Applicant	Round 2026.7 for use in the pharmaceutical industry
3204 17 00		8480717/2025	Colorant C.I. Pigment Violet 23 (CAS RN 215247-95-3) and preparations based on it with a content of colorant C.I. Pigment Violet 23 of 70 % by weight or more	<u>S</u>	New	UNDER EXAMINATION	DE	Applicant	Round 2026.7 to be used in pigments preparations
3204 90 00		8824649/2025	Preparation containing by weight of - more than 25 % but not more than 30 % of Oxirane, 2-methyl-, polymer with oxirane, ether with bis(4-(bis(2-hydroxyethyl)amino)phenyl)(2-	<u>S</u>	New	UNDER EXAMINATION	BE	Applicant	Round 2026.7 to be used for the production of polyurethane

			<p>sulfophenyl)methyl (4:1), monosodium salt, block (CAS RN 126042-89-5) and;</p> <ul style="list-style-type: none"> <li>- More than 15 % but not more than 20 % of Polyethylene-polypropylene glycol (CAS RN 9003-11-6) and;</li> <li>- More than 25 % but not more than 30 % of Oxirane, 2-methyl-,polymer with oxirane, ether with 2,2'-((3-methyl-4-((4-methyl-2-benzothiazolyl)azo)phenyl)imino)bis(ethanol)(2:1) (CAS RN 229306-55-2) and;</li> <li>- More than 5 % but not more than 10 % of Oxirane, 2-methyl-,polymer with oxirane, ether with 5-(2-(4-(bis(2-hydroxyethyl)amino)-2-methylphenyl)diazanyl)-3-methyl-2,4-thiophenedicarbonitrile (2:1) (CAS RN 515857-23-5) and;</li> <li>- More than 15 % but not more than 20 % of Oxirane, 2-methyl-,polymer with oxirane, ether with ethyl 3-(4-bis(2-hydroxyethyl)amino)phenyl)-2-cyano-2-propenoate (2:1) (CAS RN 152286-82-3)</li> </ul>						
3204 90 00		8823689/2025	<p>Preparation containing by weight of</p> <ul style="list-style-type: none"> <li>- more than 90 % but not more than 99 % of Oxirane, 2-methyl-,polymer with oxirane, ether with ethyl 3-(4-(bis(2-hydroxyethyl)amino)phenyl)-2-cyano-2-propenoate (2:1) (CAS RN 152286-82-3) and;</li> <li>- More than 1 % but not more than 10 % of Polyethylene-polypropylene glycol (CAS RN 9003-11-6)</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	BE	Applicant	Round 2026.7 to be used for polyurethane
3204 90 00		8824224/2025	<p>Preparation containing by weight of</p> <ul style="list-style-type: none"> <li>- more than 23 % but not more than 36 % of Oxirane, 2-methyl-,polymer with oxirane, ether with bis(4-(bis(2-hydroxyethyl)amino)phenyl)(2-sulfophenyl)methyl (4:1), monosodium salt, block (CAS RN 126042-89-5) and;</li> <li>- More than 4 % but not more than 20 % of</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	BE	Applicant	Round 2026.7 for the manufacture of polyurethane

			<p>Polyethylene-polypropylene glycol (CAS RN 9003-11-6) and;</p> <ul style="list-style-type: none"> <li>- More than 25 % but not more than 30 % of Oxirane, 2-methyl-,polymer with oxirane, ether with 2,2'-((3-methyl-4-((4-methyl-2-benzothiazolyl)azo)phenyl)imino)bis(ethanol)(2:1) (CAS RN 229306-55-2) and;</li> <li>- More than 5 % but not more than 10 % of Oxirane, 2-methyl-,polymer with oxirane, ether with 5-(2-(4-(bis(2-hydroxyethyl)amino)-2-methylphenyl)diazanyl)-3-methyl-2,4-thiophenedicarbonitrile (2:1) (CAS RN 515857-23-5) and;</li> <li>- More than 15 % but not more than 25 % of Oxirane, 2-methyl-,polymer with oxirane, ether with ethyl 3-(4-bis(2-hydroxyethyl)amino)phenyl)-2-cyano-2-propenoate (2:1) (CAS RN 152286-82-3)</li> </ul>						
3204 90 00		8823831/2025	<p>Preparation containing by weight of</p> <ul style="list-style-type: none"> <li>- More than 5 % but not more than 15 % of Polyethylene-polypropylene glycol (CAS RN 9003-11-6) and;</li> <li>- More than 85 % but not more than 95 % of Oxirane, 2-methyl-,polymer with oxirane, ether with 5-(2-(4-(bis(2-hydroxyethyl)amino)-2-methylphenyl)diazanyl)-3-methyl-2,4-thiophenedicarbonitrile (2:1) (CAS RN 515857-23-5)</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	BE	Applicant	Round 2026.7 for the production of polyurethane
3204 90 00		8823937/2025	<p>Preparation containing by weight of</p> <ul style="list-style-type: none"> <li>- more than 40 % but not more than 60 % of Oxirane, 2-methyl-, polymer with oxirane, ether with 2,2'-[[3-methyl-4-[(4-methyl-2-benzothiazolyl)azo]phenyl]imino]bis[ethanol] (2:1) (CAS RN 229306-55-2) and;</li> <li>- More than 40 % but not more than 60 % of Polyethylene-polypropylene glycol (CAS RN 9003-11-6)</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	BE	Applicant	Round 2026.7 to be used in production of polyurethane

3204 90 00		8824141/2025	Preparation containing by weight of - more than 50 % but not more than 70 % of Oxirane, methyl-polymer with oxirane, ether with bis(4-[bis(2-hydroxyethyl)amino)phenyl] (2-sulfophenyl)methyl (4:1), monosodium salt block (CAS RN 126042-89-5) and; - More than 30 % but not more than 50 % of Polyethylene-polypropylene glycol (CAS RN 9003-11-6)	<u>S</u>	New	UNDER EXAMINATION	BE	Applicant	Round 2026.7 to be used in the manufacture of polyurethane
3204 90 00		8824032/2025	Preparation containing by weight of - more than 60 % but not more than 80 % of Oxirane, 2-methyl-,polymer with oxirane, ether with 2,2',2'',2'''-(sulfonylbis(4,1-phenylene)-2,1-diazenediyl(3-methyl-4,1-phenylene)nitrilo)tetrakis(ethanol) (4:1) (CAS RN 927432-39-1) and; - More than 20 % but not more than 40 % of Polyethylene-polypropylene glycol (CAS RN 9003-11-6)	<u>S</u>	New	UNDER EXAMINATION	BE	Applicant	Round 2026.7 to be used in the production of polyurethane
3403 11 00		8427256/2025	Lubricating preparation contains by weight - 40 % or more but note more than 60 % silicone (CAS RN: 63394-02-5) - 30 % or more but note more than 50 % hydrocarbon (CAS RN: 308067-53-0) based mineral oils lubricants - 5 % or more but not more than 15 % specialty additives to provide anti-block, cohesive, and antistatic properties, designed specifically for production of spandex fiber	<u>S</u>	New	UNDER EXAMINATION	TR	Applicant	Round 2026.7 to be used in the spandex yarn industry
3801 10 00		8484406/2025	Artificial graphite, electrically conductive raw material for batteries	<u>S</u>	New	UNDER EXAMINATION	HU	Applicant	Round 2026.07 Artificial graphite for batteries
3810 10 00		8495844/2025	Tin or zink based, halide free SMT processing solder paste: - with metal contents of 87,5 % or more, but	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026/07 used for assembly of electronic systems of a

			<p>not more than 90,1 % by weight,</p> <ul style="list-style-type: none"> <li>- with an alloy solidus temperature of 210oC or more,</li> <li>- with a viscosity of 178 Pa·s or more, but not more than 235 Pa·s,</li> <li>- with fines grind of 40 um or less,</li> <li>- with a silver content either of 3,15 % or more, but not more than 3,5 % by weight for tin based paste or of 0,25 % or more, but not more than 0,28 % by weight for zinc based paste,</li> <li>- with or without bismuth content of 2,55 % or more, but not than 2,71 % by weight,</li> <li>- with or without copper content of 0,6 % or more, but not more than 0,7 % by weight</li> </ul>						kind used in automotive industry
3815 12 00		8427494/2025	<p>Catalyst used to obtain paraxylene and orthoxylene by isomerization of methaxylene containing by weight:</p> <ul style="list-style-type: none"> <li>- Aluminium Oxide (CAS RN 1344-28-1) not more than 95 %,</li> <li>- Aluminosilicate (CAS RN 1327-36-2) not more than 15 %,</li> <li>- Platinum (CAS RN 7440-06-4) not more than 2 %</li> <li>- Aluminium Chloride Hydroxide (CAS RN 12042-91-0) not more than 2 %</li> <li>- Hydrogen Sulfide (CAS RN 7783-06-4) not more than 0,2 %</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	TR	Applicant	Round 2026/07 used in production of paraxylene and orthoxylene
3815 19 90		8933271/2025	<p>Catalyst for use in the production of acrylonitrile, consisting of a mixture of metal oxides fixed to a silicon dioxide support in powder form, containing 20 % or more but not more than 40 % by weight of molybdenum, bismuth and iron.</p>	<u>S</u>	New	UNDER EXAMINATION	TR	Applicant	Round 2026.7 to be used in the production of acrylonitrile
3815 19 90		8934646/2025	<p>Catalyst, in the form of powder, consisting of a mixture of metal oxides fixed on a support of silicon dioxide, with a total content by weight of</p>	<u>S</u>	New	UNDER EXAMINATION	DE	Applicant	Round 2026.7 for the production of acrylonitrile

			molybdenum, bismuth and iron of 20 % or more but not more than 50 %, for the preparation in the manufacture of acrylonitrile						
3815 90 90		8427437/2025	Catalyst used to remove mercaptans contained in LPG by oxidation, in liquid form, containing by weight; - Complex cobalt components not more than 30 % and water	<u>S</u>	New	UNDER EXAMINATION	TR	Applicant	Round 2026/07 for use in LPG production
3902 90 90		8241545/2025	1-Octene Homopolymer Hydrogenated	<u>S</u>	New	UNDER EXAMINATION	BE	Applicant	Round 2026.7 to be used in processed oils
3907 30 00		8675096/2025	Epoxy resin (CAS RN 1675-54-3) containing by weight; <ul style="list-style-type: none"> <li>- 40 % but not more than 60 % xylene (CAS RN 1330-207-7),</li> <li>- not more than 0,1 % free hydrolyzed sodium chloride (CAS RN 7647-14-5),</li> </ul> specially produced for electronic circuits, electrical isolators and coatings	<u>S</u>	New	UNDER EXAMINATION	TR	Applicant	Round 2026.7 for electrical insulators and high-voltage-resistant coatings
3907 30 00		8675176/2025	Epoxy resin (CAS RN 1675-54-3) containing by weight <ul style="list-style-type: none"> <li>- 1 % but not more than 20 % bisphenol (CAS RN 80-05-7),</li> <li>- not more than 0.1 % free hydrolyzable chloride (CAS RN 7647-14-5),</li> <li>- not more than 0.1 % sodium chloride (CAS RN 7647-14-5).</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	TR	Applicant	Round 2026.7 for use in flexible composite solutions
3907 40 00		8427019/2025	Polycarbonate (CAS RN 235420-85-6) of phosgene and bisphenol A: <ul style="list-style-type: none"> <li>- containing by weight 12 % or more but not more than 26 % of a copolymer of isophthaloyl chloride, terephthaloyl chloride and resorcinol,</li> <li>- with p-cumylphenol endcaps, and</li> <li>- with a weight average molecular weight (Mw) of 29900 or more but not more than 31900</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	NL	Applicant	Round 2026.7 to produce pelletized compounds used in various industries

3910 00 00		8495877/2025	<p>Low outgassing thermally conductive silicone paste:</p> <ul style="list-style-type: none"> <li>- with thermal conductivity when cured of 3,45 W/(m·K) or more but not more than 3,55 W/(m·K),</li> <li>- with continuous use temperature range between -60 °C and 200 °C or more,</li> <li>- with heat capacity when cured of 0,75 J/g·K or more but not more than 0,85 J/g·K,</li> <li>- with volume resistivity when cured of 1010 Ω·m or more,</li> <li>- packaged in containers of 30 kg or bigger</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.7 to be used in PCBs for cooling devices
3919 90 80		8329858/2025	<p>Self-adhesive plastic plate, printed, also shaped:made of polycarbonate film type Makrofol DE 1-4,</p> <ul style="list-style-type: none"> <li>- with a thickness of 0.3 mm or more, but not more than 0.4 mm,</li> <li>- with minimal dimensions 63 mm x 15 mm</li> <li>- with maximum dimensions 278 mm x 117 mm</li> <li>- with a weight of not more than exceeding 5 g per piece,</li> </ul> <p>intended for integration into combined instrument panels of passenger cars</p>	<u>S</u>	New	UNDER EXAMINATION	SK	Applicant	Round 2026.7 for use in passenger cars panels
3920 62 19		8495754/2025	<p>High-performance print grade of poly(ethylene terephthalate) (PET) film in rolls with:</p> <ul style="list-style-type: none"> <li>- a thickness of 35 µm or more, but not more than 75 µm,</li> <li>- a tensile strength of at least 40 MPa in the machine direction (MD) and at least 200 MPa in the transverse direction (TD),</li> <li>- an elongation at break of at least 400 % in MD and at least 30 % in TD,</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.7 for the production of shrink sleeve labels

			<ul style="list-style-type: none"> <li>- a heat shrinkage (at 90 degrees Celsius for 10 seconds) in MD of 0,49 % or more, but not more than 0,51 %,</li> <li>- a heat shrinkage dynamic in TD of no more than 20 percentage points between 55°C and 70°C,</li> <li>- a light transmittance equal to or greater than 85 %,</li> <li>- a haze ratio equal to or less than 6 %,</li> <li>- a surface tension equal to or greater than 38 mN/m,</li> <li>- with a density of 1.30 g/cm<sup>3</sup> or more, but not more than 1.34 g/cm<sup>3</sup>,</li> <li>- a shelf life declared by the manufacturer of not less than 12 months</li> </ul>						
3921 19 00		8480639/2025	<p>Thermal Runaway Protection Pads,</p> <ul style="list-style-type: none"> <li>- made from closed-cell silicone foam,</li> <li>- with a thickness of 2.0 mm or more but not more than 4.8 mm,</li> <li>- a thermal insulation of 0.33 Km<sup>2</sup>/W (according to ASTM-C518)</li> <li>- a dielectric strength of 3.4 Kv/mm (according to ASTM- D149)</li> </ul>	<u>S</u>	<b>New</b>	UNDER EXAMINATION	DE	Applicant	Round 2026.7 for battery cells
3921 90 55		8480332/2025	<p>Flexible prepreg sheets or rolls made of modified epoxy resin without the use of halogenated flame retardants with embedded glass fabric</p> <ul style="list-style-type: none"> <li>- with a TG &gt;145°C and &lt; 200° according to TMA</li> <li>- with a classification according to IPC-4101/128 or 4101/130 or IPC-4101/153 or 4101/154</li> </ul>	<u>S</u>	<b>New</b>	UNDER EXAMINATION	DE	Applicant	Round 2026.7 for the production of printed circuit boards
5401 10 14		8377501/2025	<p>Poly/poly core-spun yarns made from polyester high tenacity filament yarn as a core:</p> <ul style="list-style-type: none"> <li>- covered with the staple polyester fibres,</li> <li>- with a twist of 410 TPM or more, but not more than 1200 TPM,</li> <li>- with a linear density of 200 dtex or more,</li> </ul>	<u>S</u>	<b>New</b>	UNDER EXAMINATION	PL	Applicant	Round 2026.7 for the production of polyester threads

			<p>but not more than 1500 dtex,</p> <ul style="list-style-type: none"> <li>- with an average minimum tenacity of 46 cN/tex,</li> <li>- with an elongation of 13 % or more, but not more than 23 %,</li> <li>- wound on the perforated dyeing tube ready for dyeing,</li> <li>- with a weight including the tube of 900 g or more</li> </ul>						
5402 20 00		8377465/2025	<p>High tenacity polyester filament yarn:</p> <ul style="list-style-type: none"> <li>- with final twist of Z direction,</li> <li>- with a linear density of 100 dtex or more, but not more than 4000 dtex,</li> <li>- with an average minimum tenacity of 64 cN/tex,</li> <li>- with an elongation of 12 % or more, but not more than 28 %,</li> <li>- with a shrinkage in 98oC of 0 % or more, but not more than 3,5 %,</li> <li>- wound on the perforated dyeing tube ready for dyeing</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.7 used in threads for furniture manufacturing
5503 90 00		8669165/2025	<p>Staple fibres fully encapsulated by polyethylene sheath with PET core with:</p> <ul style="list-style-type: none"> <li>- a linear density of 0,60 dtex or more, but not more than 1,99 dtex,</li> <li>- a staple length of 37 mm or more, but not more than 44 mm,</li> <li>- an elongation at break equal to or greater than 80 %,</li> <li>- a minimum tenacity of 1 cN/dtex</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.7 used in the industry of hygiene products
6804 21 00		8446586/2025	<p>Wheels suitable for grinding, rounding, polishing, aligning or cutting:</p> <ul style="list-style-type: none"> <li>- of natural or synthetic diamonds which are agglomerated with metal, metal alloy, glass, ceramic, or resin,</li> <li>- whether or not containing a hole in the</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	CZ	Applicant	Round 2026.7 to be used in the industry of semiconductor wafers

			<p>centre,</p> <ul style="list-style-type: none"> <li>- with an external diameter not more than 870 mm,</li> </ul> <p>of a kind used for machines for the manufacture of semiconductor wafers.</p> <p>(1)</p>						
6814 10 00		8241393/2025	<p>Phlogopite Mica Tape bonded to reinforced material of non-alkaline glass fabric or polyethylene film with high temperature resistant silicone resin,</p> <ul style="list-style-type: none"> <li>- with a thickness of 0.10mm (+0.015mm) or more but not more than 16mm,</li> <li>- with a width of 500mm or more but not more than 1200mm, a mica content of 80g/m<sup>2</sup> (+3 g/m<sup>2</sup>) but not more than 165 g/m<sup>2</sup>,</li> <li>- a tensile strength of 110N/cm or more but not more than 130N/cm</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	BE	Applicant	Round 2026.7 to be used for fire resistant wire and cable
6814 90 00		8484277/2025	<p>Li-ion battery module component made of mica (MICA) for fire protection, with a specially designed shape for the top and sides</p>	<u>S</u>	New	UNDER EXAMINATION	HU	Applicant	Round 2026.07 Li-ion battery module component made of mica for fire protection
7002 20 90		8495786/2025	<p>Glass preforms made of high-purity silica (quartz) glass with an optical core made of germanium-doped silica (quartz) glass, intended for the production of low-loss optical fiber:</p> <ul style="list-style-type: none"> <li>- 90 % of all preforms preforms weigh between 46 kg and 50 kg, with an average weight of 46,2 kg,</li> <li>- the maximum length of the preform is 2500 mm,</li> <li>- diameter of the preform ranges between 115 mm and 139 mm, with the average diameter of 127 mm,</li> <li>- the preforms contain a handle with a diameter of 25,4 mm, coated at the end with</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.7 to be used in the production of optical fiber

			aluminum oxide, allowing the preform to be suspended in the preform holder of the optical fiber manufacturing device						
7115 90 00		8427632/2025	A paste used in solar cell production containing 80-95 % Silver Powder, 1-10 % Isobutyric acid, 0.1-1 % Fatty acid salts of Polyamide by weight	<u>S</u>	New	UNDER EXAMINATION	TR	Applicant	Round 2026.7 used in solar cell production
8110 90 00		8426962/2025	Antimony-Beryllium pellets containing by weight : - 20 % or more but not more than 25 % of beryllium (CAS 7440-41-7) - 77 % or more but not more than 83 % of antimony (CAS 7440-36-0)	<u>S</u>	New	UNDER EXAMINATION	FR	Applicant	Round 2026.7 used in nuclear power plant
8409 91 00		8329795/2025	The exhaust gas recirculation assembly consisting of: - a control unit, - an air throttle, - an intake pipe, - an outlet hose, for use in the manufacture of spark-ignition piston internal combustion engines of motor vehicles  (1)	<u>S</u>	New	UNDER EXAMINATION	SK	Applicant	Round 2026.07 The exhaust gas recirculation assembly for use in the manufacture of combustion engines of motor vehicles
8414 30 20		8426646/2025	Hermetic compressor for R600a refrigerant for the production of refrigerators and freezers; - with a power not exceeding 0,4 kW, - pre filled with lubricant from 130 ml to 180 ml, - suction and processing pipe inner diameter from 6.10 mm to 6.60 mm, - discharge pipe inner diameter from 4.80 mm to 5.00 mm, - driven by AC electric motor, - cooling capacity from 137 to 184 W at 3000 rpm, - displacement from 7.5 cm <sup>3</sup> to 10.5 cm <sup>3</sup> .  (1)	<u>S</u>	New	UNDER EXAMINATION	TR	Applicant	Round 2026.07 compressor for production of refrigerators and freezers

8414 30 20		8495675/2025	Refrigeration compressor for R-600a as refrigerant with: <ul style="list-style-type: none"> <li>- pre-charged with the mineral lubricant oil with oil charge 180 cm<sup>3</sup> or more, but not more than 220 cm<sup>3</sup>,</li> <li>- with a brushless DC electric motor (BLDC),</li> <li>- without inverter controller,</li> <li>- weight of 6,2 kg or more, but not more than 6,8 kg,</li> <li>- with aluminium or copper motor winding,</li> <li>- with left side injection from suction line,</li> <li>- with displacement 5 cm<sup>3</sup> or more, but not more than 8,8 cm<sup>3</sup>,</li> <li>- speed of 1020 rpm or more, but not more than 4 800 rpm,</li> <li>- with an output power of 5 W or more, but not more than 300 W</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.07 Refrigeration compressor
8414 59 35		8669363/2025	DC motor centrifugal fans with: • a nominal voltage of 8 V or more, but not more than 13 V, • a nominal max speed of 1400 rpm or more, but not more than 1950 rpm, • a horizontal or vertical shaft position of fan blades, • boosting time of 10 seconds or less, • a cable with RAST 2,5 connector of length of 30 cm or more, but not more than 50 cm, • a nominal power of 0,7 W or more, but not more than 3,5 W, • with tachometer or feedback signal to monitor the speed RAST = Raster-Anschluss-Steck-Technik	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.07 DC motor centrifugal fans for refrigerator
8418 99 90		8669318/2025	Condenser being a type of heat exchanger made entirely of aluminum A3102 / A3003 / A4045 / A4343, consisting of two vertical pipes, including one with inlet and outlet tubes, and 16 arranged horizontally and in parallel, flat tubes with placed fins between them, with: <ul style="list-style-type: none"> <li>- a width of 297 mm or more, but not more than 373 mm,</li> <li>- a height of 154 mm or more but not more than 158 mm,</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.07 Condenser used in refrigerator

			<ul style="list-style-type: none"> <li>- a depth of 17 mm or more but not more than 23 mm,</li> <li>- a flatness smaller than 2 mm,</li> <li>- a weight of 224g or more, but not more than 283 g</li> </ul>						
8483 20 00		8484102/2025	Commutator End Shield for the starter motors of passenger cars and commercial vehicles • produced with high pressure precision die casting technology; • made of aluminium alloy with numerical designation EN AC-46000 or EN AC-46000 S, according to the DIN EN 1706 standard; • without bearing	<u>S</u>	New	UNDER EXAMINATION	HU	Applicant	Round 2026.07 Commutator End Shield for the starter motors of passenger cars and commercial vehicles
8483 50 80		8627782/2025	Metal spinned single or double pulley: <ul style="list-style-type: none"> <li>- made of DC03 steel or similar non alloy steel or free cutting steel,</li> <li>- with a pitch diameter of 67 mm or more but not more than 145 mm,</li> <li>- with an inner hole designed for bearing mounting or key mounting</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.07 Metal spinned single or double pulley for manufacturing gardening tools and machinery
8483 50 80		8627698/2025	Metal spinned triple pulley: <ul style="list-style-type: none"> <li>- made of DC03 steel or similar non-alloy steel or free cutting steel,</li> <li>- with a pitch diameter of 60 mm or more, but not more than 130 mm,</li> <li>- with an inner hole designed for bearing mounting</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.07 Metal spinned triple pulley for manufacturing gardening tools and machinery
8483 60 80		8484181/2025	Overrunning clutch for passenger car and commercial vehicle starter motors • with total length of at least 49.4 mm but not more than 210 mm; • tooth number of starting-motor pinion: at least 9 but not more than 16 pieces	<u>S</u>	New	UNDER EXAMINATION	HU	Applicant	Round 2026.07 Overrunning clutch for passenger car and commercial vehicle starter motors
8501 32 00		8621903/2025	Electric Permanent Magnet Synchronous Motor	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.07

			<p>with:</p> <ul style="list-style-type: none"> <li>- a rotor containing 8 poles generated by permanent magnets composed mainly with praseodymium-neodymium-iron-boron (per GB/T 13560-2017 standard) enclosed in stainless steel cover,</li> <li>- an outer diameter of motor magnet shaft end with dimension of 10,001 mm or more, but no more than 10,007 mm,</li> <li>- a motor terminals located across the radius 37,00 mm and separated by an angle of 30,00 °,</li> <li>- a motor housing made of ADC12 (EN AC46000) aluminum alloy die casting with composition of aluminum-silicon-copper (per JIS H5302-2000 or EN 1706 standard),</li> <li>- a back electromotive force constant (Ke) of 0,0265 V-sec/rad or more, but no more than 0,0293 V-sec/rad,</li> <li>- a back electromotive force harmonic order: 5th no more than 0,4 % (of fundamental) and 7th no more than 0,2 % (of fundamental),</li> <li>- a synchronous inductance of 33,49 μH or more, but no more than 37,01 μH,</li> <li>- a cogging torque of no more than 15 mNm,</li> <li>- a friction torque in ambient temperature of no more than 20 mNm,</li> <li>- a maximum temperature of motor operation of no more than 200 °C</li> </ul>						Electric permanent magnet synchronous motor for manufacture of the electric power steering system in a motor vehicle
8503 00 20		8483412/2025	Plated steel core of the electric motor stator of electric air conditioning compressors for motor vehicles:• with an outer diameter of at least 90 mm but not more than 120 mm,• with an inner diameter of at least 65 mm but not more than 80 mm,• with a height of at least 30 mm but not more than 45 mm,• with a weight of at least 0,7 kg but not more than 1,2 kg.	<u>S</u>	New	UNDER EXAMINATION	HU	Applicant	Round 2026.07 Plated steel core of the electric motor stator of electric air conditioning compressors for motor vehicles

8503 00 20		8483954/2025	Plated steel core of the electric motor rotor of electric air conditioning compressors for motor vehicles: • with an outer diameter of at least 65 mm but not more than 80 mm, • with an inner diameter of at least 15 mm but not more than 25 mm, • with a height of at least 30 mm but not more than 45 mm, • with a weight of at least 0,5 kg but not more than 0,8 kg.	<u>S</u>	New	UNDER EXAMINATION	HU	Applicant	Round 2026.07 Plated steel core of the electric motor rotor of electric air conditioning compressors for motor vehicles
8503 00 98		8484022/2025	Armature for the starter motors of passenger cars and commercial vehicles - with an outer diameter of at least 52 mm but not more than 80 mm; - with a commutator copper wire diameter of at least 2 mm but not more than 4 mm	<u>S</u>	New	UNDER EXAMINATION	HU	Applicant	Round 2026.07 Armature for the starter motors of passenger cars and commercial vehicles
8511 90 00		8484229/2025	Drive end shield for starter motors and alternators of passenger cars and commercial vehicles • produced with high pressure precision die casting technology; • made of aluminium alloy with numerical designation EN AC-47100 or EN AC-47100 S or EN AC-46000 or EN AC-46000 S or EN AC-44300 according to DIN EN 1706 standard; • without bearing	<u>S</u>	New	UNDER EXAMINATION	HU	Applicant	Round 2026.07 Drive end shield for starter motors and alternators of passenger cars and commercial vehicles
8511 90 00		8484137/2025	Drive end shield for starter motors and alternators of passenger cars and commercial vehicles • produced with high pressure precision die casting technology; • made of aluminium alloy with numerical designation EN AC-47100 or EN AC-47100 S or EN AC-46000 or EN AC-46000 S or EN AC-44300 according to DIN EN 1706 standards; • with bearing	<u>S</u>	New	UNDER EXAMINATION	HU	Applicant	Round 2026.07 Drive end shield for starter motors and alternators of passenger cars and commercial vehicles
8511 90 00		8484067/2025	Commutator for passenger car and commercial vehicle starter motors • with a length of at least 27.7 mm but not more than 44.6 mm; • with umbrella or drum design	<u>S</u>	New	UNDER EXAMINATION	HU	Applicant	Round 2026.07 Commutator for passenger car and commercial vehicle starter motors
8516 80 80		8669241/2025	Electric heating resistor with a triple loop design,	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.07

			<p>intended for heating water in automatic household washing machines:</p> <ul style="list-style-type: none"> <li>- mainly made of AISI 316L stainless steel,</li> <li>- with a rated voltage of 230V,</li> <li>- with a rated power of 2000W,</li> <li>- with a total heating element length of 217 mm or more, but not more than 223 mm,</li> <li>- with a working length of the heating element of 169,5 mm or more, but not more than 174,5 mm,</li> <li>- with a mounting flange diameter of 28 mm or more, but not more than 32 mm,</li> <li>- with a heating element bending radius of 10,75 mm,</li> <li>- equipped with thermal fuses,</li> <li>- without a built-in NTC sensor,</li> <li>- with nickel plated terminal pin and connector</li> </ul>						Electric heating resistor with a triple loop design, intended for heating water in automatic household washing machines
8538 90 99		8627835/2025	<p>Controller covers made of aluminum AISi9Cu alloy (EN AC-46000) with:</p> <ul style="list-style-type: none"> <li>- heat radiating functionality,</li> <li>- a volume as-cast lower than 128 000 mm<sup>3</sup>,</li> <li>- a volume machined lower than 126 000 mm<sup>3</sup>,</li> <li>- a length and width of 130 mm or lower,</li> <li>- a height of 40 mm or lower,</li> <li>- a wall thickness of 2,5 mm or more but no more than 16 mm,</li> <li>- a 6 to 20 mounting screw holes diameter 2,5 mm or more, but no more than 4,0 mm and tolerance for diameter required as 0,05 mm,</li> <li>- with critical assembly areas where flatness is defined as of 0,1 mm,</li> <li>- tolerance machining of 0,05 mm or lower diameter tolerance and flatness of 0,1 mm or lower</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.07 Controller covers for manufacturing of the automotive steering systems
8544 30 00		8329599/2025	High voltage battery cable assembly comprising at	<u>S</u>	New	UNDER	SK	Applicant	Round 2026.07 The

			<p>least:</p> <ul style="list-style-type: none"> <li>- single core high voltage cable terminated with a flat lug,</li> <li>- safety fuse for an electric current of 10 A or more but not more than 400 A,</li> <li>- flat copper conductor with surface insulation,</li> <li>- three or more plastic clips for attachment for use in the production of rechargeable batteries for hybrid and electric vehicles</li> </ul> <p>(1)</p>			EXAMINATION			high-voltage battery cable assembly used for connecting battery cell assemblies
8544 30 00		8329746/2025	<p>High-voltage single-core battery supply cable comprising at least:</p> <ul style="list-style-type: none"> <li>- a high-voltage connector,</li> <li>- a metal flat lug with an eyelet in a plastic housing,</li> <li>- three or more plastic mounting clips</li> </ul> <p>for use in the production of rechargeable batteries for hybrid and electric vehicles</p> <p>(1)</p>	<u>S</u>	New	UNDER EXAMINATION	SK	Applicant	Round 2026.07 High-voltage battery supply cable for the positive pole
8544 30 00		8329712/2025	<p>A wiring harness for transmitting safety parameters from battery modules comprising at least:</p> <ul style="list-style-type: none"> <li>- input and output connectors,</li> <li>- three or more plastic mounting clips</li> </ul> <p>for use in the production of rechargeable batteries for hybrid and electric vehicles</p> <p>(1)</p>	<u>S</u>	New	UNDER EXAMINATION	SK	Applicant	Round 2026.07 A wiring harness for use in the production of rechargeable batteries for hybrid and electric vehicles
8544 42 90		8669200/2025	<p>Wire harness for power supply connection to printed board assembly (PBA ):</p> <ul style="list-style-type: none"> <li>- with connectors used in electrical components of rider frontmowers, hedge Trimmers, chainsaws, brushcutters, blowers and Li-Ion Batteries,</li> <li>- composed of wires with crimped wire-to-board connectors,</li> <li>- bundled with rubber, vinyl, electrical tape,</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.07 Wire harness for power supply connection to printed board assembly (PBA )

			<p>conduit, a weave of extruded string or a combination of thereof,</p> <ul style="list-style-type: none"> <li>- for the transmission of signals and/or electrical power</li> </ul>						
8548 00 90		8627638/2025	<p>An Electromagnetic Interference (EMI) filter designed to eliminate conducted electromagnetic interference from the power line, mounted at the power input of automatic washing machines:</p> <ul style="list-style-type: none"> <li>- Rated voltage: 250 V AC</li> <li>- Rated current: no more than 15 A</li> <li>- Operating frequency: 50/60 Hz</li> <li>- Dielectric strength: 1500V AC for 1 minute</li> <li>- Containing a bleeder resistor with a resistance of 470 kΩ</li> <li>- Containing three varistors for rated voltage equal to 681V, 910V and 1800V</li> <li>- Mounted with an M8 screw with an average breaking force of 93 kgf/cm</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.07 An Electromagnetic Interference (EMI) filter for production of the automatic washing machines
8708 94 99		8621762/2025	<p>Assist pinion made of carbon steel alloy steel per ISO BG/T 3077, 20CrMo, with:</p> <ul style="list-style-type: none"> <li>- a carburized part surface,</li> <li>- a surface hardness of 58 HRC or more, but no more than 63 HRC (per Hardness Rockwell scale C),</li> <li>- a length of 113,15 mm or more but not more than 113,85 mm,</li> <li>- an outer diameter of 21,7 mm or more, but not more than 21,8 mm,</li> <li>- 7 teeth,</li> <li>- a knurling on an outer surface of major diameter 27,98 mm or more but not more than 28,08 mm</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.07 Assist pinion for manufacture of the vehicle steering systems
8708 94 99		8621740/2025	<p>Blank Asm worm gear consisting of hub made of carbon steel (per GB/T 699 grade 25 or DIN EN</p>	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.07 Blank Asm worm gear for

			10277 grade 11 SMn 30) and ring made of cast polyamide 6/12 with: <ul style="list-style-type: none"> <li>- an outer diameter of 97,35 mm or more, but not more than 102,65 mm,</li> <li>- an inner diameter of 27,91 mm or more, but not more than 27,93 mm,</li> <li>- a height of the Hub of 11,75 mm or more, but not more than 12,00 mm,</li> <li>- an overall height of 16,00 mm or more, but not more than 18,00 mm</li> </ul>						manufacture of the steering gearboxes for vehicle control systems
8708 94 99		8621785/2025	Steering rack made of carbon steel JIS G 4051 S45C Modified Steel with: <ul style="list-style-type: none"> <li>- a minimal yield strength of 690 MPa,</li> <li>- an induction harden tooth section and back side of the rack teeth with hardness of 54 HRC or more, but no more than 60 HRC (per Hardness Rockwell scale C),</li> <li>- a maximum length of 666,55 mm or more but not more than 667,05mm,</li> <li>- an outer diameter of 25,944 mm or more, but not more than 28 mm,</li> <li>- a 31 teeth on rack assist side and 30 teeth on rack handweel side,</li> <li>- M14 internal threads on both ends</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.07 Steering rack for manufacture of the vehicle steering systems
8708 94 99		8495929/2025	Inner tie rod made with SCM440 JIS G 4053 steel designed for mounting to the vehicle knuckle and steering rack, with: <ul style="list-style-type: none"> <li>- a housing made with GB/T699 grade 20 steel,</li> <li>- a ball seat made of polyoxymethylene plastic,</li> <li>- a diameter of tie rod housing equal to 41.00 mm,</li> <li>- a distance from the end of tie rod to plane facing rack steering of 205,6 mm, 213,6 mm, or 233,6 mm,</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.07 Inner tie rod used in the manufacture of vehicle's steering system

			<ul style="list-style-type: none"> <li>- a thread connecting outer tie rod and inner tie rod, with dimensions of M14 x 1.5 6g,</li> <li>- a ball stud mounted to the end of tie rod with distance of 184,2 mm or more, but no more than 213,8 mm,</li> <li>- lubricant</li> <li>- for use in the manufacture of vehicle's steering system</li> </ul>						
8708 94 99		8621855/2025	<p>Steering pinion made of carbon steel alloy steel (per JIS G4052 GRADE SCM415H) with:</p> <ul style="list-style-type: none"> <li>- a carburized surface with an exception of t-bar hole,</li> <li>- a surface hardness of 58 HRC or more but not more than 63 HRC (per Hardness Rockwell scale C),</li> <li>- a length of 143,08 mm or more but not more than 143,78 mm,</li> <li>- an outer diameter of 26,65 mm or more, but not more than 28,05 mm,</li> <li>- with pinion of 10 or 11 teeth,</li> <li>- an inner diameter of 6,55 mm or more but not more than 6,70 mm</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.07 Steering pinion for manufacture of the vehicle steering systems
8708 99 97		8495712/2025	<p>Inner pole electromagnet core used in MR (Magneto-Rheological) engine mount to reduce shocks, and for isolation and damping in passenger cars, with:</p> <ul style="list-style-type: none"> <li>- a maximum diameter of 90,95 mm,</li> <li>- an overall height of 24,5mm,</li> <li>- powder metal assembly,</li> <li>- an impregnated with sealant,</li> <li>- a zinc plated</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.07 Inner pole electromagnet core used in MR (Magneto-Rheological) engine mounts used in automotive applications.
8708 99 97		8495981/2025	<p>Outer tie rod with a housing made with of 40Cr GB/T 3077 steel, with:</p> <ul style="list-style-type: none"> <li>- a ball stud made of E6SCM440 JIS G 4053</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.07 Outer tie rod for use in the manufacture of

			<p>steel,</p> <ul style="list-style-type: none"> <li>- a ball seat made of polyoxymethylene plastic,</li> <li>- a distance between the end of the threaded hole and the centre of the ball stud of 213,00 mm,</li> <li>- a ball stud diameter of 25,00 mm,</li> <li>- with a threaded hole depth of 47,5 mm, with dimensions of M14 x 1,5,</li> <li>- a boot seal,</li> <li>- a boot seal protector and retaining ring,</li> <li>- lubricant</li> </ul> <p>for use in the manufacture of vehicle's steering system</p>						vehicle's steering system
9401 99 20		8495825/2025	<p>Latch seat system modules enabling seat sliding, latching and unlatching in random, independent positions along the rails:</p> <ul style="list-style-type: none"> <li>- with an integrated safety locking mechanism,</li> <li>- with a cassette architecture for integration with seat through screw connections,</li> <li>- with an anti-noise system,</li> <li>- interfacing with car rail systems,</li> <li>- without electronic control unit,</li> <li>- without semiconductors,</li> <li>- with a weight of 1475 g or more but not more than 1619 g</li> </ul>	<u>S</u>	New	UNDER EXAMINATION	PL	Applicant	Round 2026.07 Latch seat system modules enabling seat sliding in motor vehicles
<p>ex 1511 90 19 ex 1511 90 91 ex 1513 11 10 ex 1513 19 30 ex 1513 21 10 ex 1513 29 30</p>	<p>20 20 20 20 20 20</p>	<p>1/1/1999 PROLONG 2022 PROLONG 2025</p>	<p>DE 15.09.2025 new text description: Palm oil, coconut (copra) oil, palm kernel oil, for the manufacture of:</p> <ul style="list-style-type: none"> <li>- industrial monocarboxylic fatty acids of subheading 3823 19 10,</li> <li>- methyl esters of fatty acids of heading 2915 or 2916,</li> <li>- fatty alcohols of subheadings 2905 17, 2905 19 and 3823 70 used for the preparation of cosmetics, washing products or pharmaceutical</li> </ul>	<u>S</u>	Amendment	UNDER EXAMINATION	<p>BE DE DE ES EU EU FR NL NL NL</p>	<p>Applicant Applicant Applicant Applicant Applicant Applicant</p>	Round 2026.07 Amendment request

			<p>products,</p> <ul style="list-style-type: none"> <li>- fatty alcohols of subheading 2905 16, pure or mixed, for the preparation of cosmetics, washing products or pharmaceutical products,</li> <li>- stearic acid of subheading 3823 11 00,</li> <li>- goods of heading 3401, or</li> <li>- fatty acids with high purity of heading 2915</li> </ul> <p>-----</p> <p>Palm oil, coconut (copra) oil, palm kernel oil, for the manufacture of:</p> <ul style="list-style-type: none"> <li>- industrial monocarboxylic fatty acids of subheading 3823 19 10,</li> <li>- methyl esters of fatty acids of heading 2915 or 2916,</li> <li>- fatty alcohols of subheadings 2905 17, 2905 19 and 3823 70 used for the manufacture of cosmetics, washing products or pharmaceutical products,</li> <li>- fatty alcohols of subheading 2905 16, pure or mixed, used for the manufacture of cosmetics, washing products or pharmaceutical products,</li> <li>- stearic acid of subheading 3823 11 00,</li> <li>- goods of heading 3401, or</li> <li>- fatty acids with high purity of heading 2915</li> </ul> <p>(1)</p>						
ex 1515 90 99	92	1959/1/2002 PROLONG 2019 PROLONG 2024 PROLONG 2025	Vegetable oil, refined or semi-refined, containing by weight 35 % or more but not more than 57 % of arachidonic acid or 35 % or more but not more than 50 % of docosahexaenoic acid	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	DE ES IE	Applicant Applicant Applicant	Round 2026.07 Review of the measure Ingredient to manufacture infant formula nutritional products arachidonic acid = icoso-5,8,11,14-tetraenoic acid = cis,cis,cis,cis-5,8,11,14-icosatetraenoic acid docosahexaenoic acid = doconexent (INN) = cis-4,7,10,13,16,19-

									docosahexaenoic acid
ex 1517 90 99 1518 00 99	30	833/06 PROLONG 2022	<p>NL 03.07.2025 For the ARA products (suspension): Vegetable and/or microbial oil, refined, containing by weight:</p> <ul style="list-style-type: none"> <li>- 25 % or more but not more than 70 % arachidonic acid</li> <li>- not more than 5 % docosahexenoic acid, standardized with vegetable oil</li> </ul> <p>and For the EPA/DHA products (quota): Vegetable and/or microbial oil, refined, containing by weight:</p> <ul style="list-style-type: none"> <li>- 10 % or more but not more than 80 % of eicosapentaenoic acid</li> <li>- a minimum eicosapentaenoic acid/(eicosapentaenoic acid + docosahexenoic acid) ratio of more than 20 %, standardized with vegetable oil</li> </ul> <p>---</p> <p>FR 14.05.2025 (supported by BG 16.05) Vegetable and/or microbial oil, refined, containing by weight:</p> <ul style="list-style-type: none"> <li>- 25 % or more but not more than 70 % arachidonic acid and no more than 5 % docosahexaenoic acid standardized with vegetable oil</li> </ul> <p>---</p> <p>NL new proposal: Vegetable and/or microbial oil, whether or not refined, containing by weight:</p> <ul style="list-style-type: none"> <li>- 25 % or more but not more than 70 % arachidonic acid and no more than 5 % docosahexenoic acid, or</li> <li>- 10 % or more but not more than 80 % of eicosapentaenoic acid and a minimum ratio of EPA/(EPA+DHA) over 20 %, standardized with vegetable oil</li> </ul>	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	BG BG EU EU FR FR NL	Applicant Applicant Applicant Applicant Applicant Applicant Applicant	Round 2026-01- request for amendment.// trade names : DHA and ARA oils (Arasco & Dhasco)

			<p>***</p> <p>Current description: Vegetable and/or microbial oil, refined, containing by weight:</p> <ul style="list-style-type: none"> <li>- 25 % or more but not more than 70 % arachidonic acid and no more than 5 % docosahexenoic acid, or</li> <li>- 10 % or more but not more than 80 % of eicosapentaenoic acid and a minimum ratio of EPA/(EPA+DHA) over 20 %, standardized with vegetable oil</li> </ul>						
ex 2835 10 00	20	3058712/2013 PROLONG 2019 PROLONG 2024 PROLONG 2025	<p>DE 15.9.2025 new text description: Sodium hypophosphite (CAS RN 7681-53-0) with a purity by weight of 97 % or more or as aqueous solution containing by weight 55 % or more but not more than 65 %</p> <p>----- Sodium hypophosphite (CAS RN 7681-53-0)</p>	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	DE FR	Applicant Applicant	Round 2026/07 request for amendment ROUND 2014-07-01 intended use: Incorporation in the formulations of chemical plating and/or raw material for flame retardant
ex 2841 70 00	30	2996043/2014 PROLONG 2020 PROLONG 2025	<p>DE 15.9.2025 requested amended description: Hexaammonium heptamolybdate, anhydrous (CAS RN 12027-67-7) or as tetrahydrate (CAS RN 12054-85-2) with a purity by weight of 98 % or more</p> <p>----- Hexaammonium heptamolybdate, anhydrous (CAS RN 12027-67-7) or as tetrahydrate (CAS RN 12054-85-2)</p>	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	BE DE	Applicant Applicant	Round 2026/07 amendment request ROUND 2015-07 Product used for production of hydrodesulfurisation catalysts
ex 2842 10 00	60	1345815/2016	<p>NL 15.09.2025 Requested new description: Aluminosilicate (CAS RN 1318-02-1) with</p> <ul style="list-style-type: none"> <li>- a purity by weight of 94 % or more,</li> <li>- a zeolite structure of aluminophosphate-eighteen (AEI), and</li> <li>- a phase purity of 90 % or more</li> </ul> <p>for use in the manufacture of copper zeolite or washcoat used in the automotive catalyst production</p> <p>-----</p>	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	DE ES NL	Applicant Applicant Applicant	Round 2026.07 Amendment request ROUND 2017-01 Component will be used in the manufacture of automotive catalyst

			Aluminosilicate (CAS RN 1318-02-1) with - a purity by weight of 94 % or more, - a zeolite structure of aluminophosphate-eighteen (AEI), and - a phase purity of 90 % or more for use in the manufacture of copper zeolite (1)						
ex 2903 99 80	50	1289/2008 PROLONG 2019 PROLONG 2024 PROLONG 2025	DE 15.09.2025 Requested amended description: Fluorobenzene (CAS RN 462-06-6) with a purity by weight of 99 % or more ----- Fluorobenzene (CAS RN 462-06-6)	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	DE DE FR	Applicant Applicant Applicant	Round 2026.07 Amendment request
ex 2904 99 00	80	3078740/2014 3078765/2014 PROLONG 2020 PROLONG 2025	DE 15.9.2025 requested amended description: 1-Chloro-2-nitrobenzene (CAS RN 88-73-3) with a purity by weight of 99 % or more ----- 1-Chloro-2-nitrobenzene (CAS RN 88-73-3)	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	DE DE DE	Applicant Applicant Applicant	Round 2026/07 amendment request End-use: Used in the paints industry and the printing inks industry, for pigment preparation
ex 2906 19 00	50	555842/2014 PROLONG 2020 PROLONG 2025	4-tert-Butylcyclohexanol (CAS RN 98-52-2)	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	DE DE	Applicant Applicant	Round 2026/07 amendment request ROUND 2015-01-01 4-tert-Butylcyclohexanol is used in the manufacture of p-tert-Butylcyclohexyl chloroformate (CAS RN 42125-46-2).
ex 2914 19 90	30	1046/2007 PROLONG 2023	DE 15.9.2025 requested amended description: 3-Methylbutanone (CAS RN 563-80-4) with a purity by weight of 97 % or more ----- 3-Methylbutanone (CAS RN 563-80-4)	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	DE NL	Applicant Applicant	Round 2026/07 amendment request alternative name : isopropylmethylketone
ex 2914 39 00	30	1013/2007 PROLONG	DE 15.9.2025 new text description: Benzophenone (CAS RN 119-61-9) with a purity	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	DE IT	Applicant Applicant	Round 2026/07 request for amendment

		2023	by weight of 99 % or more ----- Benzophenone (CAS RN 119-61-9)						trade name : BZQ
ex 2918 29 00	50	1301/3/1994 PROLONG 2019 PROLONG 2024 PROLONG 2025	DE 15.9.2025 requested amended description: Hexamethylene bis[3-(3,5-di-tert-butyl-4- hydroxyphenyl)propionate] (CAS RN 35074-77- 2) with a purity by weight of 97 % or more ----- Hexamethylene bis[3-(3,5-di-tert-butyl-4- hydroxyphenyl)propionate] (CAS RN 35074-77- 2)	<u>S</u>	<b>Amendme nt</b>	UNDER EXAMINATION	DE DE	Applicant Applicant	Round 2026/07 amendment request  1,6-Hexandiolbis-3- (3,5-di-tert-butyl-4- hydroxyphenyl)propion at
ex 2921 42 00	35	847/05 PROLONG 2019 PROLONG 2024 PROLONG 2025	DE 15.9.2025 requested amended description: 2-Nitroaniline (CAS RN 88-74-4) with a purity by weight of 99 % or more ----- 2-Nitroaniline (CAS RN 88-74-4)	<u>S</u>	<b>Amendme nt</b>	UNDER EXAMINATION	DE DE	Applicant Applicant	Round 2026/07 amendment request
ex 2921 49 00	40	1996/1/2001 PROLONG 2019 PROLONG 2024 PROLONG 2025	15.9.2025 DE requested amended description: N-1-Naphthylaniline (CAS RN 90-30-2) with a purity by weight of 98 % or more ----- N-1-Naphthylaniline (CAS RN 90-30-2)	<u>S</u>	<b>Amendme nt</b>	UNDER EXAMINATION	DE FR	Applicant Applicant	Round 2026/07 amendment request
ex 2924 19 00	60	975/06 PROLONG 2022	DE 15.09.2025 Requested amended description: N,N-Dimethylacrylamide (CAS RN 2680-03-7) with a purity by weight of 97 % or more ----- N,N-Dimethylacrylamide (CAS RN 2680-03-7)	<u>S</u>	<b>Amendme nt</b>	UNDER EXAMINATION	DE	Applicant	Round 2026.07 Amendment request short name : DMAA
ex 2924 29 70	17	662655/2014 PROLONG 2020 PROLONG 2025	DE 15.09.2025 Requested amended description: 2-(Trifluormethyl)benzamid (CAS RN 360-64-5) with a purity by weight of 98 % or more ----- 2-(Trifluormethyl)benzamid (CAS RN 360-64-5)	<u>S</u>	<b>Amendme nt</b>	UNDER EXAMINATION	DE	Applicant	Round 2026.07 Amendment request ROUND 2015-01-01 Manufacture of a plant protection product // Fungicide (protection of plants from fungal

									attack)
ex 2925 11 00	30	462/2/1985 PROLONG 2019 PROLONG 2024 PROLONG 2025	1,2-benzisothiazol-3(2H)-one 1,1-dioxide (CAS RN 81-07-2) or sodium 1,2-benzothiazol-3-olate 1,1-dioxide (CAS RN 128-44-9) with a purity by weight of 98 % or more	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	DE	Applicant	Round 2026.07 Amendment request
ex 2928 00 90	10	446/1/1981 PROLONG 2019 PROLONG 2024 PROLONG 2025	DE 15.09.2025 Requested amended description: 3,3'-Bis(3,5-di-tert-butyl-4-hydroxyphenyl)-N,N'-bipropionamide (CAS RN 32687-78-8) with a purity by weight of 97 % or more ----- 3,3'-Bis(3,5-di-tert-butyl-4-hydroxyphenyl)-N,N'-bipropionamide (CAS RN 32687-78-8)	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	DE	Applicant	Round 2026.07 Amendment request
ex 2928 00 90	55	311617/2013 PROLONG 2019 PROLONG 2024 PROLONG 2025	Aminoguanidinium hydrogen carbonate (CAS RN 2582-30-1)	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	CZ DE	Applicant Applicant	Round 2026.07 Amendment request ROUND 2014-01-01 >> Commercial denomination: Aminoguanidine bicarbonate >> End-use: organic intermediate product for the manufacture of pigments
ex 2933 69 80	45	1286961/2018 PROLONG 2024 PROLONG 2025	DE 15.09.2025 Requested amended description: 2-(4,6-Bis-(2,4-dimethylphenyl)-1,3,5-triazin-2-yl)-5-(octyloxy)-phenol (CAS RN 2725-22-6) with a purity by weight of 98 % or more ----- 2-(4,6-Bis-(2,4-dimethylphenyl)-1,3,5-triazin-2-yl)-5-(octyloxy)-phenol (CAS RN 2725-22-6)	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	DE IT	Applicant Applicant	Round 2026.07 Amendment request ROUND 2019-01 This substance is used in the following products: polymers e in particular building materials, agricultural films, adhesives and sealants, coating products and cosmetics and personal care products

ex 2934 99 90	25	130914/2010 PROLONG 2016 PROLONG 2021	NL 15.09.2025 Requested amended description 2,4-Diethyl-9H-thioxanthen-9-one (CAS RN 82799-44-8) with a purity by weight of 97 % or more ----- 2,4-Diethyl-9H-thioxanthen-9-one (CAS RN 82799-44-8)	<u>S</u>	<b>Amendme nt</b>	UNDER EXAMINATION	NL	Applicant	Round 2026.07 Amendment request
ex 2935 90 90	56	3702997/2015 PROLONG 2021	N-(p-Toluenesulphonyl)-N'-(3-(p- toluenesulphonyloxy)phenyl)urea (CAS RN 232938-43-1)	<u>S</u>	<b>Amendme nt</b>	UNDER EXAMINATION	DE EU	Applicant Applicant	Round 2026/07 review of the suspension ROUND 201607 Phenol-free color developer for thermal paper
ex 3204 15 00	25	6633361/2024	Mixture in a 3:2 ratio of colourants C.I. Vat Blue 1 potassium salt (CAS RN 835912-68-0) and C.I. VAT Blue 1 sodium salt (CAS RN 894-86-0) and preparations based thereon with a combined content of colourants C.I. Vat Blue 1 salts of 40 % or more by weight	<u>S</u>	<b>Amendme nt</b>	UNDER EXAMINATION	TR TR	Applicant Applicant	Round 2026.07 - Objection Round 2025/7 - for use in the textile industry
ex 3809 91 00	20	6559753/2024	TR 15.09.2025 Requested amended description: Aqueous antimony pentoxide mixture containing by weight: • 46 % or more but not more than 55 % of antimony pentoxide (CAS RN 1314- 60-9)• 1 % or more but not more than 10 % of triethanolamine (CAS RN 102-71-6) or 1 % or more but not more than 10 % of triethanolamine phosphate (CAS RN 10017-58-6) ----- Aqueous antimony pentoxide mixture containing by weight: - 48 % or more but not more than 55 % of antimony pentoxide (CAS RN 1314-60-9), - 1 % or more but not more than 5 % of triethanolamine (CAS RN 102-71-6)	<u>S</u>	<b>Amendme nt</b>	UNDER EXAMINATION	TR	Applicant	Round 2026.07 Amendment request 2025/7 - Flame retardant to be used in modacrylic fiber
ex 3811 21 00 3811 90 00	10	596/6/1987 PROLONG 2019	NL 15.09.2025 Amended description: Solution of mineral oils (CAS RN 64742-52-5, 64742-53-6, 64742-56-9 or blends thereof) containing by	<u>S</u>	<b>Amendme nt</b>	UNDER EXAMINATION	NL	Applicant	Round 2026.07 Amendment and double classification

		PROLONG 2024 PROLONG 2025	weight: - 25 % or more but not more than 55 % of the barium, calcium, magnesium or zinc salt of dinonylnaphthylsulphonic acid (CAS RN 25619-56-1, 28015-99-8, 28016-00-4, or 57855-77-3) - whether or not, not more than 25 % of the barium, calcium, magnesium or zinc salt of a mixture of C3-C24 carboxylic acids (CAS RN 68990-37-4) ----- Salts of dinonylnaphthalenesulphonic acid, in the form of a solution in mineral oils						request
ex 3815 12 00	10	1023/1/1980 PROLONG 2019 PROLONG 2024 PROLONG 2025	DE 15.09.2025 Requested amended description: Catalyst in the form of granules, wheels or ring-shaped structures - of a diameter of 3 mm or more, but not exceeding 10 mm, - containing 8 % or more but not more than 40 % by weight of silver - on a carrier based on aluminium oxide, - with one or more promoters ----- Catalyst, in the form of granules or rings of a diameter of 3 mm or more but not more than 10 mm, consisting of silver on an aluminium oxide support and containing by weight 8 % or more but not more than 40 % of silver	<u>S</u>	<b>Amendme nt</b>	UNDER EXAMINATION	BE LU	Applicant Applicant	Round 2026.07 Amendment request
ex 3815 90 90	80	279/4/1996 PROLONG 2015 PROLONG 2016 PROLONG 2021	NL 15.9.2025 new text description: Catalyst in isobutanol (CAS RN 78-83-1), containing by weight: - 50 % or more but not more than 65 % of dinonylnaphthalenedisulphonic acid (CAS RN 60223-95-2) ----- Catalyst consisting predominantly of dinonylnaphthalenedisulphonic acid in the form of a solution in isobutanol	<u>S</u>	<b>Amendme nt</b>	UNDER EXAMINATION	NL	Applicant	Round 2026/07 request for amendment

ex 3906 90 90	33	1138473/2015 PROLONG 2021	<p>New text proposal: Mixture containing by weight:</p> <ul style="list-style-type: none"> <li>- 80 % but not more than 90 % of Core shell polymer of butyl acrylate, ethyl acrylate, methyl-acrylate and allyl methacrylate (CAS RN 73026-23-0) and</li> <li>- 10 % but not more than 20 % of copolymer of methyl methacrylate and ethyl acrylate (CAS RN 9010-88-2)</li> </ul> <p>--</p> <p>Old text: Core shell copolymer of butyl acrylate and alkyl methacrylate, with a particle size of 5 µm or more but not more than 10 µm</p>	<u>S</u>	<b>Amendme nt</b>	UNDER EXAMINATION	DE FR	Applicant Applicant	Round 2026.7 Request for amendment ROUND 01-2016:incorporation in thermoplastics extrusion process
ex 3919 90 80	51	1702/16/2002/v2 PROLONG 2019 PROLONG 2024 PROLONG 2025	<p>NL 15.09.2025 Amended description: Biaxially-oriented film of poly(methyl methacrylate), of a thickness of 20 µm or more but not exceeding 90 µm, covered on one side with an adhesive layer and a release sheet</p> <p>-----</p> <p>Biaxially-oriented film of poly(methyl methacrylate), of a thickness of 50 µm or more but not exceeding 90 µm, covered on one side with an adhesive layer and a release sheet</p>	<u>S</u>	<b>Amendme nt</b>	UNDER EXAMINATION	DE	Applicant	Round 2026.07 Amendment request
ex 3926 90 97	77	5560026/2016 PROLONG 2022	<p>PL 15.09.2025 Proposed text modification: Silicone decoupling ring with an inner diameter of 13,2 mm or more but no more than 17,2 mm, in immediate packings of 2 500 pieces or more, of a kind used in car parking aid sensor systems</p> <p>-----</p> <p>Silicone decoupling ring with an inner diameter of 14,7 mm or more but not more than 16,0 mm, in immediate packings of 2 500 pieces or more, of a kind used in car parking aid sensor systems</p>	<u>S</u>	<b>Amendme nt</b>	UNDER EXAMINATION	FR	Applicant	Round 2026.07 Amendment request  Decoupling rings contribute to the manufacturing of sensors used in automotive driving assistance systems, mainly for park assist (ULS - Ultrasonic Parking Sensor). Decoupling rings provide sealing and insulating functions to protect the sensor

									from external vibrations.
5602 10 19		2281825/2025	<p>DE 15.07.2025 Needle-punched spunbond nonwovens, consisting of polyamide fibres individually coated with polyvinylalcohol, containing by weight 20 % or more but not more than 40 % of polyvinylalcohol weighing XX g/m2</p> <p>--</p> <p>NL 04.06.2025 (Accepted by TR on 17.6) Needle punched felt, consisting of polyamide fibres individually coated with polyvinylalcohol, containing by weight 20 % or more but not more than 40 % of polyvinylalcohol</p> <p>--</p> <p>TR 10.06.2025 Not impregnated, coated, covered or laminated needle punched felt ,</p> <ul style="list-style-type: none"> <li>- fibers of the felt contain polyvinyl alcohol content of 20 % or more but not more than 40 %</li> </ul> <p>--</p> <p>NL 04.06.2025 (Accepted by TR on 17.6) Needle punched felt, consisting of polyamide fibres individually coated with polyvinylalcohol, containing by weight 20 % or more but not more than 40 % of polyvinylalcohol</p> <p>--</p> <p>Needle punched felt with a polyvinyl alcohol content of 20 % or more but not more than 40 %</p>	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	TR	Applicant	Round 2026.1 to be used in the manufacture of microfiber synthetic leather
ex 8406 81 00	10	6501845/2024	<p>DE 15.09.2025 amendment proposal: Industrial steam turbine with:</p> <ul style="list-style-type: none"> <li>- an output of 40 MW or more but not more than 90 MW,</li> <li>- designed for a pressure of not more than 165 bar and a temperature of not more than 565 ° C,</li> <li>- equipped with individually controlled single or double seat valves on the live steam side which are operated with a hydraulic servo of</li> </ul>	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	DE EU	Applicant Applicant	Round 2026.07 amendment request Round 2025/7 used for the production of power generation units

			<p>not more than 30 bar</p> <p>-----</p> <p>Industrial steam turbine with:</p> <ul style="list-style-type: none"> <li>- an output of more than 40 MW but not more than 90 MW,</li> <li>- designed for a pressure of not more than 165 bar and a temperature of not more than 565 °C,</li> <li>- equipped with double seat valves on the live steam side which are operated with a hydraulic servo of not more than 30 bar</li> </ul>						
ex 8418 99 90	40	6662970/2024	<p>PL 15.09.2025 amendment proposal:</p> <p>An evaporator being a type of heat exchanger, consisting of aluminium pipes with copper ends enclosed with aluminium radiators:</p> <ul style="list-style-type: none"> <li>- measuring 337 x 237 x 17 mm or more, but not more than 868 x 399 x 78 mm,</li> <li>- with a total weight of a set of 236 g or more, but not more than 1 750 g,</li> <li>- with a fixed sensor,</li> <li>- with noise absorber,</li> <li>- with 2, 5 or 7 control and power connection pins terminated with sensor temperature, heater or fuse type of socket,</li> </ul> <p>for use in the manufacture of products of subheadings 8418 10, 8418 21, 8418 40</p> <p>-----</p> <p>An evaporator being a type of heat exchanger, consisting of aluminium pipes with copper ends enclosed with aluminium radiators:</p> <ul style="list-style-type: none"> <li>- measuring 403 x 276 x 70 mm or more, but not more than 464 x 399 x 83 mm,</li> <li>- with a total weight of a set of 236 g or more, but not more than 1 010 g,</li> <li>- with a fixed sensor,</li> <li>- with noise absorber,</li> <li>- with 2, 5 or 7 control and power connection pins terminated with sensor temperature, heater or fuse type of socket,</li> </ul>	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	EU PL	Applicant Applicant	Round 2026.07 amendment request Round 2025/7 for use in the manufacture of freezers or refrigerators

			for use in the manufacture of products of subheadings 8418 10, 8418 21, 8418 40 (1)						
ex 8504 31 80	30	1195/2008 PROLONG 2019 PROLONG 2024 PROLONG 2025	SK 15.09.2025 new text proposal: Transformers, having a power handling capacity of not more than 1 kVA for use in the manufacture of static converters and goods of heading 8537. ----- ---- Switching transformers, having a power handling capacity of not more than 1 kVA for use in the manufacture of static converters (1)	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	SK	Applicant	Round 2026.07 amendment request
ex 8507 60 00	26	6609698/2023	IT 15.9.2025 new text description: Modules for the assembly of electric accumulators using lithium ferrophosphate technology (LFP) with: - a length of 670 mm or more, but not more than 882 mm, - a width of 390 mm or more, but not more than 655 mm, - a height of 110 mm or more, but not more than 155 mm, - a weight of 60 kg or more, but not more than 165 kg, and - a power of 11 300 Wh or more, but not more than 29 360 Wh ----- Modules for the assembly of electric accumulators using lithium ferrophosphate technology (LFP) with: - a length of 670 mm or more, but not more than 882 mm, - a width of 390 mm or more, but not more than 655 mm, - a height of 110 mm or more, but not more than 137 mm, - a weight of 60 kg or more, but not more than 165 kg, and - a power of 11 300 Wh or more, but not	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	DE EU EU EU	Applicant Applicant Applicant Applicant	Round 2026/07 request for amendment Round 2024/07 used for assembly of ion lithium electric accumulators, which will be incorporated in battery electric vehicles.

			more than 29 360 Wh						
ex 8507 60 00	33	1232310/2015	Lithium-ion battery module or accumulator, with: <ul style="list-style-type: none"> <li>- a length of 150 mm or more, but not more than 1 310 mm,</li> <li>- a width of 100 mm or more, but not more than 1 000 mm,</li> <li>- a height of 200 mm or more, but not more than 1 500 mm,</li> <li>- a weight of 50 kg or more, but not more than 200 kg,</li> <li>- cells of a nominal capacity of 58 Ah or more but not more than 500Ah,</li> <li>- a nominal output voltage of 230 V AC or 45 V or more but not more than 980 V DC</li> </ul>	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	EU EU EU EU NL PL TR	Applicant Applicant Applicant Applicant Applicant Applicant	Round 2026-07: Roll-over Round 2026-01: review of the suspension/prolongation 1 year ROUND 01-2016 The product is a battery pack for use in a stationary energy storage application.
ex 8537 10 91	75	6633310/2024	HU 15.09.2025 Proposed text modification: Printed circuit board equipped with a microcontroller for operating and/or control purposes <ul style="list-style-type: none"> <li>- with or without operating components, signal components and display,</li> <li>- for operating voltages of 5V DC or more but not more than 24V DC or 220V AC or more but not more than 400V AC,</li> </ul> for use in the manufacture of household appliances of subheadings 7321 11, 8414 60, 8418 10, 8418 21, 8418 29, 8418 40, 8422 11, 8450 11, 8450 12, 8450 19, 8450 20, 8451 21, 8451 29, 8516 60 ----- Printed circuit board equipped with a microcontroller for operating and/or control purposes <ul style="list-style-type: none"> <li>- with or without operating components, signal components and display,</li> <li>- for operating voltages of 5V DC or more but not more than 12V DC or 220V AC or more but not more than 400V AC,</li> </ul> for use in the manufacture of household appliances of subheadings 7321 11, 8414 60, 8418	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	EU HU	Applicant Applicant	Round 2026.07 amendment request Round 2025.7 - control circuit boards for household appliances

			10, 8418 21, 8418 29, 8418 40, 8422 11, 8450 11, 8450 12, 8450 19, 8450 20, 8451 21, 8451 29, 8516 60 (1)						
ex 8544 30 00 ex 8544 42 90	40 40	847787/2014 PROLONG 2020 PROLONG 2025	HU 15.09.2025 proposed description: Wire harness or cable for steering system or motor vehicle rear-view systems: - for an operating voltage of 12V or 24V, - with connectors on both sides, - whether or not with anchor clamps of plastic for mounting on a motor vehicle steering box ----- Wire harness or cable for steering system: - for an operating voltage of 12 V, - with connectors on both sides, - whether or not with anchor clamps of plastic for mounting on a motor vehicle steering box	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	SK	Applicant	Round 2026.07 amendment request ROUND 2015-01 Sensor harness is used to connect the torque sensor with electro-motor in belt drive steering system.
ex 8708 95 99	50	5870000/2021	SK 15.09.2025 Requested amended description Airbag inflator containing pyrotechnics, whether or not cold gas, as propellant for safety airbags of vehicles, in each individual consignment of 1 000 pieces or more ----- Airbag inflator containing both pyrotechnics and cold gas as propellant for safety airbags of vehicles, in each individual consignment of 1 000 pieces or more	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	HU	Applicant	Round 2026.07 amendment request Round 2022/7 Hybrid inflators for production of passenger safety airbags
ex 9002 11 00	85	3076474/2014 PROLONG 2025	DE 15.09.2025 new text proposal Lens with - a horizontal field of view of 20° or more, but not more than 220°, - a focal length of 1.16 mm or more, but not more than 20 mm, - a relative aperture of f/1.2 or more, but not more than f/4, and - a diameter of 5 mm or more, but not more than 40 mm, - for use in the manufacture of CMOS vehicle-mounted cameras or IP network	<u>S</u>	<b>Amendment</b>	UNDER EXAMINATION	IE	Applicant	Round 2026.07 amendment request ROUND 2015-07 Using a camera module align assembly, the lenses are accurately aligned into the automotive camera assembly in a five axis alignment, fixed in position with an epoxy resin and they are

			cameras ----- Lens assembly with: <ul style="list-style-type: none"> <li>- a horizontal field of view range of 20 deg or more, but not more than 200 deg,</li> <li>- a focal length of 1,16 mm or more, but not more than 20 mm,</li> <li>- a relative aperture of F/1,2 or more, but not more than F/4, and</li> <li>- a diameter of 5 mm or more, but not more than 40 mm,</li> </ul> for use in the manufacture of CMOS automotive cameras or in IP network cameras production (1)							calibrated and image tested.
--	--	--	--	--	--	--	--	--	--	------------------------------

(1) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013.

DISCLAIMER: The duty suspension and quota requests on the following list are currently under discussion. The data available on this list may not represent the final state of the discussions within the relevant Commission Working group. Please note that it cannot be guaranteed that the information available exactly reproduces an officially adopted text. Only European Union legislation published in the Official Journal of the European Union is deemed authentic.



2025/1292

30.6.2025

**COUNCIL REGULATION (EU) 2025/1292**

**of 23 June 2025**

**amending Regulation (EU) 2021/2283 opening and providing for the management of autonomous tariff quotas of the Union for certain agricultural and industrial products**

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty on the Functioning of the European Union, and in particular Article 31 thereof,

Having regard to the proposal from the European Commission,

Whereas:

- (1) In order to ensure a sufficient supply of certain agricultural and industrial products which are produced in insufficient quantities in the Union and thereby avoid any disturbances on the market for those products, autonomous tariff quotas of the Union ('quotas') were opened by Council Regulation (EU) 2021/2283<sup>(1)</sup>. Within those quotas, products can be imported into the Union at reduced or zero duty rates.
- (2) As it is in the Union's interest to ensure an adequate supply of certain industrial products, and having regard to the fact that identical, equivalent or substitute products are not produced in sufficient quantities within the Union, it is necessary to open new quotas with order numbers 09.2010, 09.2017, 09.2024, 09.2025, 09.2027, 09.2029, 09.2031 at zero duty rates for appropriate quantities of those products, as of 1 July 2025.
- (3) As the scope of the quota with order number 09.2585 has become inadequate to fulfil the needs of economic operators in the Union, TARIC codes 3907 61 00 20 and 3907 69 00 20 should be added to this quota as of 1 July 2025.
- (4) As it is no longer in the Union's interest to maintain the quotas with order numbers 09.2563, 09.2808, and 09.2925, those quotas should be closed with effect from 1 July 2025.
- (5) In response to the Russian Federation's ongoing war of aggression against Ukraine and the continued involvement of the Republic of Belarus in actions undermining Ukraine's sovereignty and territorial integrity, the Union has adopted restrictive measures aimed at limiting trade benefits granted to Russia and Belarus. Council Regulation (EU) 2022/2563<sup>(2)</sup> introduced an exception to the application of customs duties under autonomous tariff quotas for certain products originating in Russia and Belarus, specifically for quotas with order numbers 09.2600, 09.2742, 09.2698, and 09.2835, covering products falling under TARIC codes ex 2712 90 39 10, ex 2926 10 00 10, ex 3204 17 00 30, and ex 7604 29 10 30, respectively. Given the persistence of the geopolitical situation and the need to reinforce the effectiveness of the Union's response, it is appropriate to discontinue that exception and to reinstate the application of customs duties on imports originating in Russia and Belarus under those quotas. Taking that measure ensures consistency with the Union's restrictive trade policy and prevents economic benefits from being conferred upon entities operating in or supporting actions contrary to international law.
- (6) Taking into account the amendments to be made and for the sake of clarity, the Annex to Regulation (EU) 2021/2283 should be replaced.
- (7) Regulation (EU) 2021/2283 should therefore be amended accordingly.
- (8) In order to avoid any interruption in the application of the quota scheme and to comply with the guidelines set out in the communication from the Commission of 13 December 2011 concerning autonomous tariff suspensions and quotas, the changes provided for in this Regulation regarding the quotas for the products concerned should apply from 1 July 2025. This Regulation should therefore enter into force as a matter of urgency,

<sup>(1)</sup> Council Regulation (EU) 2021/2283 of 20 December 2021 opening and providing for the management of autonomous tariff quotas of the Union for certain agricultural and industrial products, and repealing Regulation (EU) No 1388/2013 (OJ L 458, 22.12.2021, p. 33, ELI: <http://data.europa.eu/eli/reg/2021/2283/oj>).

<sup>(2)</sup> Council Regulation (EU) 2022/2563 of 19 December 2022 amending Regulation (EU) 2021/2283 opening and providing for the management of autonomous tariff quotas of the Union for certain agricultural and industrial products (OJ L 330, 23.12.2022, p. 109, ELI: <http://data.europa.eu/eli/reg/2022/2563/oj>).

HAS ADOPTED THIS REGULATION:

*Article 1*

Regulation (EU) 2021/2283 is amended as follows:

(1) in Article 1, paragraph 4 is replaced by the following:

‘4. The suspension laid down in paragraph 2 does not apply to products originating in Russia or in Belarus, including for quota order numbers 09.2600, 09.2742, 09.2698, and 09.2835. Consequently, imports of such products originating in Russia and Belarus shall be subject to the Common Customs Tariff duties as from 1 July 2025.’;

(2) the Annex is replaced by the text set out in the Annex to this Regulation.

*Article 2*

This Regulation shall enter into force on the day following that of its publication in the *Official Journal of the European Union*.

It shall apply from 1 July 2025.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Luxembourg, 23 June 2025.

*For the Council*

*The President*

C. SIEKIERSKI

---

ANNEX

'ANNEX

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty rate
09.2849	ex 0710 80 69	10	Mushrooms of the species <i>Auricularia polytricha</i> (uncooked or cooked by steaming or boiling), frozen, for the manufacture of prepared meals <sup>(1)</sup> <sup>(2)</sup>	1.1.-31.12.	700 tonnes	0 %
09.2913	ex 2401 10 35 ex 2401 10 70 ex 2401 10 95 ex 2401 10 95 ex 2401 10 95 ex 2401 20 35 ex 2401 20 70 ex 2401 20 95 ex 2401 20 95 ex 2401 20 95	91 10 11 21 91 91 10 11 21 91	Natural unmanufactured tobacco, whether or not cut in regular size, having a custom value of not less than EUR 450 per 100 kg net weight, for use as binder or wrapper for the manufacture of goods falling within subheading 2402 10 00 <sup>(1)</sup>	1.1.-31.12.	3 000 tonnes	0 %
09.2828	2712 20 90		Paraffin wax containing by weight less than 0,75 % of oil	1.1.-31.12.	180 000 tonnes	0 %
09.2600	ex 2712 90 39	10	Slack wax (CAS RN 64742-61-6)	1.1.-31.12.	100 000 tonnes	0 %
09.2578	ex 2811 19 80	50	Sulphamidic acid (CAS RN 5329-14-6) with a purity by weight of 95 % or more, whether or not with not more than 5 % addition of the anti-caking agent silicon dioxide (CAS RN 112926-00-8)	1.1.-31.12.	27 000 tonnes	0 %
09.2928	ex 2811 22 00	40	Silica filler in the form of granules, with a purity by weight of 97 % or more of silicon dioxide	1.1.-31.12.	1 700 tonnes	0 %

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty rate
09.2806	ex 2825 90 40	30	Tungsten trioxide, including blue tungsten oxide (CAS RN 1314-35-8 or CAS RN 39318-18-8)	1.1.-31.12.	12 000 tonnes	0 %
09.2819	ex 2833 25 00	30	Copper hydroxide sulfate (Cu <sub>4</sub> (OH) <sub>6</sub> (SO <sub>4</sub> )), hydrate (CAS RN 12527-76-3) with a purity by weight of 98 % or more	1.1.-31.12.	240 000 kilograms	0 %
09.2872	ex 2833 29 80	40	Caesium sulphate (CAS RN 10294-54-9) in solid form or as aqueous solution containing by weight 48 % or more but not more than 52 % of caesium sulphate	1.1.-31.12.	400 tonnes	0 %
09.2567	ex 2903 22 00	10	Trichloroethylene (CAS RN 79-01-6) with a purity by weight of 99 % or more	1.1.-31.12.	11 885 000 kilograms	0 %
09.2837	ex 2903 79 30	20	Bromochloromethane (CAS RN 74-97-5)	1.1.-31.12.	600 tonnes	0 %
09.2933	ex 2903 99 80	30	1,3-Dichlorobenzene (CAS RN 541-73-1)	1.1.-31.12.	2 600 tonnes	0 %
09.2700	ex 2905 12 00	10	Propan-1-ol (propyl alcohol) (CAS RN 71-23-8)	1.1.-31.12.	15 000 tonnes	0 %
09.2551	ex 2905 29 90	40	Prop-2-yn-1-ol (CAS RN 107-19-7) with a purity by weight of 99 % or more	1.1.-31.12.	150 tonnes	0 %
09.2830	ex 2906 19 00	40	Cyclopropylmethanol (CAS RN 2516-33-8)	1.1.-31.12.	20 tonnes	0 %
09.2851	ex 2907 12 00	10	O-cresol (CAS RN 95-48-7) having a purity of not less than 98,5 % by weight	1.1.-31.12.	20 000 tonnes	0 %
09.2704	ex 2909 49 80	20	2,2,2',2'-Tetrakis(hydroxymethyl)-3,3'-oxydipropan-1-ol (CAS RN 126-58-9)	1.1.-31.12.	500 tonnes	0 %
09.2010	ex 2912 29 00	75	Cyclohex-3-ene-1-carbaldehyde (CAS RN 100-50-5) with a purity by weight of 98 % or more	1.7.-31.12.	77 500 kilograms	0 %
09.2565	ex 2914 19 90	70	Calcium acetylacetonate (CAS RN 19372-44-2) with a purity by weight of 95 % or more	1.1.-31.12.	400 tonnes	0 %
09.2852	ex 2914 29 00	60	Cyclopropyl methyl ketone (CAS RN 765-43-5)	1.1.-31.12.	300 tonnes	0 %

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty rate
09.2638	ex 2915 21 00	10	Acetic acid (CAS RN 64-19-7) of a purity by weight of 99 % or more	1.1.-31.12.	1 000 000 tonnes	0 %
09.2679	2915 32 00		Vinyl acetate (CAS RN 108-05-4)	1.1.-31.12.	370 000 tonnes	0 %
09.2728	ex 2915 90 70	85	Ethyl trifluoroacetate (CAS RN 383-63-1)	1.1.-31.12.	400 tonnes	0 %
09.2665	ex 2916 19 95	30	Potassium (E,E)-hexa-2,4-dienoate (CAS RN 24634-61-5)	1.1.-31.12.	8 250 tonnes	0 %
09.2684	ex 2916 39 90	28	2,5-Dimethylphenylacetyl chloride (CAS RN 55312-97-5)	1.1.-31.12.	700 tonnes	0 %
09.2599	ex 2917 11 00	40	Diethyl oxalate (CAS RN 95-92-1)	1.1.-31.12.	500 tonnes	0 %
09.2769	ex 2917 13 90	10	Dimethyl sebacate (CAS RN 106-79-6)	1.1.-31.12.	1 000 tonnes	0 %
09.2634	ex 2917 19 80	40	Dodecanedioic acid (CAS RN 693-23-2), of a purity by weight of more than 98,5 %	1.1.-31.12.	8 000 tonnes	0 %
09.2540	ex 2917 37 00	10	Dimethyl terephthalate (CAS RN 120-61-6) with a purity by weight of 95 % or more	1.1.-31.12.	57 500 tonnes	0 %
09.2017	ex 2918 11 00	20	L-(+)-lactic acid (CAS RN 79-33-4) with a purity by weight of 99 % or more, for use in the manufacturing of: — esters and other derivatives (i.e. products obtained from a chemical reaction with the formation of new intramolecular bonds), or — solutions produced under GMP (Good Manufacturing Practice) conditions to be supplied to the pharmaceutical industry	1.7.-31.12.	27 500 tonnes	0 %
09.2646	ex 2918 29 00	75	Octadecyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (CAS RN 2082-79-3) with: — a sieve passing fraction at a mesh width of 500 µm of more than 99 % by weight, and — a melting point of 49 °C or more, but not more than 54 °C, for use in the manufacture of PVC processing stabilizer-one packs based on powder mixtures (powders or press granulates) <sup>(1)</sup>	1.1.-31.12.	380 tonnes	0 %

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty rate
09.2647	ex 2918 29 00	80	Pentaerythritol tetrakis(3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate) (CAS RN 6683-19-8) with: — a sieve passing fraction at a mesh width of 250 µm of more than 75 % by weight and at a mesh width of 500 µm of more than 99 % by weight, and — a melting point of 110 °C or more, but not more than 125 °C, for use in the manufacture of PVC processing stabilizer-one packs based on powder mixtures (powders or press granulates) (!)	1.1.-31.12.	140 tonnes	0 %
09.2975	ex 2918 30 00	10	Benzophenone-3,3',4,4'-tetracarboxylic dianhydride (CAS RN 2421-28-5)	1.1.-31.12.	1 000 tonnes	0 %
09.2598	ex 2921 19 99	75	Octadecylamine (CAS RN 124-30-1)	1.1.-31.12.	400 tonnes	0 %
09.2649	ex 2921 29 00	60	Bis(2-dimethylaminoethyl)(methyl)amine (CAS RN 3030-47-5)	1.1.-31.12.	1 700 tonnes	0 %
09.2617	ex 2921 42 00	89	4-Fluoro-N-(1-methylethyl)benzeneamine (CAS RN 70441-63-3)	1.1.-31.12.	500 tonnes	0 %
09.2602	ex 2921 51 19	10	O-phenylenediamine (CAS RN 95-54-5)	1.1.-31.12.	1 800 tonnes	0 %
09.2921	ex 2922 19 00	22	2-(dimethylamino)ethyl acrylate (CAS RN 2439-35-2) with a purity by weight of 99 % or more	1.1.-31.12.	14 000 tonnes	0 %
09.2545	ex 2922 29 00	63	Acclonifen (ISO) (CAS RN 74070-46-5) with a purity by weight of 97 % or more	1.1.-31.12.	4 000 tonnes	0 %
09.2575	ex 2923 90 00	87	3-Chloro-2-hydroxypropyl)trimethylammonium chloride (CAS RN 3327-22-8), in the form of an aqueous solution containing by weight 65 % or more but not more than 71 % 3-chloro-2-hydroxypropyl)trimethylammonium chloride	1.1.-31.12.	9 500 tonnes	0 %
09.2922	ex 2923 90 00	88	Aqueous solution containing by weight 78 % or more but not more than 82 % of [2-(acryloyloxy)ethyl]trimethylammonium chloride (CAS RN 44992-01-0)	1.1.-31.12.	10 000 tonnes	0 %
09.2854	ex 2924 19 00	85	3-Iodoprop-2-yn-1-yl butylcarbamate (CAS RN 55406-53-6)	1.1.-31.12.	450 tonnes	0 %
09.2874	ex 2924 29 70	87	Paracetamol (INN) (CAS RN 103-90-2)	1.1.-31.12.	20 000 tonnes	0 %

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty rate
09.2742	ex 2926 10 00	10	Acrylonitrile (CAS RN 107-13-1), for use in the manufacture of goods of chapter 55 and heading 6815 <sup>(1)</sup>	1.1.-31.12.	30 000 tonnes	0 %
09.2583	ex 2926 10 00	30	Acrylonitrile (CAS RN 107-13-1), for use in the manufacture of goods of headings 2921, 2924, 3903, 3906, 3908, 3911 and 4002 <sup>(1)</sup>	1.1.-31.12.	20 000 tonnes	0 %
09.2550	ex 2926 90 70	31	Lambda-cyhalothrin (ISO) (CAS RN 91465-08-6) with a purity by weight of 97 % or more	1.1.-31.12.	2 200 tonnes	0 %
09.2856	ex 2926 90 70	84	2-Nitro-4(trifluoromethyl)benzotrile (CAS RN 778-94-9)	1.1.-31.12.	900 tonnes	0 %
09.2685	ex 2929 90 90	30	Nitroguanidine (CAS RN 556-88-7)	1.1.-31.12.	6 500 tonnes	0 %
09.2597	ex 2930 90 95	94	Bis[3-(triethoxysilyl)propyl]disulphide (CAS RN 56706-10-6)	1.1.-31.12.	6 000 tonnes	0 %
09.2596	ex 2930 90 95	96	2-Chloro-4-(methylsulphonyl)-3-((2,2,2-trifluoroethoxy)methyl) benzoic acid (CAS RN 120100-77-8)	1.1.-31.12.	300 tonnes	0 %
09.2580	ex 2931 90 00	75	Hexadecyltrimethoxysilane (CAS RN 16415-12-6) with a purity by weight of at least 95 %, for use in the manufacture of polyethylene <sup>(1)</sup>	1.1.-31.12.	165 tonnes	0 %
09.2842	2932 12 00		2-Furaldehyde (furfuraldehyde)	1.1.-31.12.	10 000 tonnes	0 %
09.2024	ex 2932 19 00	85	2-Methyltetrahydrofuran (CAS RN 96-47-9) with a purity by weight of 99 % or more	1.7.-31.12.	750 tonnes	0 %
09.2696	ex 2932 20 90	25	Decan-5-olide (CAS RN 705-86-2)	1.1.-31.12.	6 000 kilograms	0 %
09.2697	ex 2932 20 90	30	Dodecan-5-olide (CAS RN 713-95-1)	1.1.-31.12.	6 000 kilograms	0 %
09.2812	ex 2932 20 90	77	Hexan-6-olide (CAS RN 502-44-3)	1.1.-31.12.	4 000 tonnes	0 %
09.2858	2932 93 00		Piperonal (CAS RN 120-57-0)	1.1.-31.12.	220 tonnes	0 %
09.2541	ex 2933 19 90	73	2,4-Dihydro-2,5-dimethyl-3H-pyrazol-3-one (CAS RN 2749-59-9) with a purity by weight of 99 % or more	1.1.-31.12.	150 tonnes	0 %

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty rate
09.2839	ex 2933 39 99	09	2-(2-Pyridyl)ethanol (CAS RN 103-74-2) with a purity by weight of 99 % or more	1.1.-31.12.	700 tonnes	0 %
09.2543	ex 2933 39 99	13	Imazamox (ISO) (CAS RN 114311-32-9) with a purity by weight of 95 % or more	1.1.-31.12.	300 tonnes	0 %
09.2546	ex 2933 39 99	46	Fluopicolide (ISO) (CAS RN 239110-15-7) with a content by weight of 97 % or more	1.1.-31.12.	250 tonnes	0 %
09.2025	ex 2933 59 95	82	Ametoctradin (ISO) (CAS RN 865318-97-4) with a purity by weight of 98 % or more	1.7.-31.12.	353 500 kilograms	0 %
09.2547	ex 2933 69 80	13	Metribuzin (ISO) (CAS RN 21087-64-9) with a purity by weight of 93 % or more	1.1.-31.12.	225 tonnes	0 %
09.2860	ex 2933 69 80	30	1,3,5-Tris[3-(dimethylamino)propyl]hexahydro-1,3,5-triazine (CAS RN 15875-13-5)	1.1.-31.12.	600 tonnes	0 %
09.2566	ex 2933 99 80	05	1,4,7,10-Tetraazacyclododecane (CAS RN 294-90-6) with a purity by weight of 96 % or more	1.1.-31.12.	60 tonnes	0 %
09.2544	ex 2933 99 80	23	Tebuconazole (ISO) (CAS RN 107534-96-3) with a purity by weight of 95 % or more	1.1.-31.12.	150 tonnes	0 %
09.2658	ex 2933 99 80	73	5-(Acetoacetyl amino)benzimidazolone (CAS RN 26576-46-5)	1.1.-31.12.	400 tonnes	0 %
09.2549	ex 2934 99 90	16	Difenoconazole (ISO) (CAS RN 119446-68-3)	1.1.-31.12.	1 000 tonnes	0 %
09.2548	ex 2934 99 90	24	Flufenacet (ISO) (CAS RN 142459-58-3) with a purity by weight of 95 % or more	1.1.-31.12.	900 tonnes	0 %
09.2593	ex 2934 99 90	67	5-Chlorothiophene-2-carboxylic acid (CAS RN 24065-33-6)	1.1.-31.12.	45 000 kilograms	0 %
09.2675	ex 2935 90 90	79	4-[[[2-Methoxybenzoyl]amino]sulfonyl]benzoyl chloride (CAS RN 816431-72-8)	1.1.-31.12.	1 000 tonnes	0 %
09.2945	ex 2940 00 00	20	D-Xylose (CAS RN 58-86-6)	1.1.-31.12.	400 tonnes	0 %
09.2686	ex 3204 11 00	75	Colourant C.I. Disperse Yellow 54 (CAS RN 7576-65-0) and preparations based thereon with a colourant C.I. Disperse Yellow 54 content of 99 % or more by weight	1.1.-31.12.	250 tonnes	0 %

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty rate
09.2676	ex 3204 17 00	14	Preparations based on Colourant C.I. Pigment Red 48:2 (CAS RN 7023-61-2) with a content thereof of 60 % or more but less than 85 % by weight	1.1.-31.12.	50 tonnes	0 %
09.2698	ex 3204 17 00	30	Colourant C.I. Pigment Red 4 (CAS RN 2814-77-9) and preparations based thereon with a colourant C.I. Pigment Red 4 content of 60 % or more by weight	1.1.-31.12.	150 tonnes	0 %
09.2659	ex 3802 90 00	19	Soda flux calcinated diatomaceous earth	1.1.-31.12.	35 000 tonnes	0 %
09.2908	ex 3804 00 00	10	Sodium lignosulphonate (CAS RN 8061-51-6)	1.1.-31.12.	40 000 tonnes	0 %
09.2889	3805 10 90		Sulphate turpentine	1.1.-31.12.	25 000 tonnes	0 %
09.2935	ex 3806 10 00	10	Rosin and resin acids obtained from fresh oleoresins	1.1.-31.12.	280 000 tonnes	0 %
09.2832	ex 3808 92 90	40	Preparation containing 38 % or more but not more than 50 % by weight of pyrithione zinc (INN) (CAS RN 13463-41-7) in an aqueous dispersion	1.1.-31.12.	500 tonnes	0 %
09.2923	ex 3808 94 20	40	Aqueous solution containing by weight: — 10,0 % or more but not more than 11,3 % of 5-chloro-2-methyl-2H-isothiazol-3-one, — 3,0 % or more but not more than 4,1 % of 2-methyl-2H-isothiazol-3-one, — a combined concentration of isothiazolones (CAS RN 55965-84-9) of 13,0 % or more but not more than 15,4 %, — 18 % or more but not more than 22 % of nitrates, calculated as sodium nitrate, and — 5 % or more but not more than 8 % of chlorides, calculated as sodium chloride	1.1.-31.12.	3 000 tonnes	0 %
09.2876	ex 3811 29 00	57	Additives consisting of reaction products of diphenylamine and branched nonenes with: — more than 20 % but not more than 50 % by weight 4-mononyldiphenylamine, and — more than 50 % but not more than 80 % by weight 4,4'-dinonyldiphenylamine, — a total percentage of 2,4-dinonyldiphenylamine and 2,4'-dinonyldiphenylamine of not more than 15 % by weight, used for the manufacture of lubricating oils <sup>(1)</sup>	1.1.-31.12.	900 tonnes	0 %

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty rate
09.2927	ex 3811 29 00	83	Additives containing by weight: — 70 % or more of 2,5-bis(tert-nonyldithio)-[1,3,4]-thiadiazole (CAS RN 89347-09-1), and — 10 % or more of 5-(tert-nonyldithio)- 1,3,4-thiadiazole-2(3H)-thione (CAS RN 97503-12-3), for use in the manufacture of blends of additives for lubricating oils <sup>(1)</sup>	1.1.-31.12.	500 tonnes	0 %
09.2027	ex 3815 19 90	82	Catalyst consisting of organo-metallic compounds of boron, titanium and aluminium, fixed on a support of silicon dioxide, in the form of powder	1.7.-31.12.	7 800 kilograms	0 %
09.2814	ex 3815 90 90	76	Catalyst consisting of titanium dioxide and tungsten trioxide	1.1.-31.12.	3 000 tonnes	0 %
09.2644	ex 3824 99 92	77	Preparation containing by weight: — 55 % or more but not more than 78 % of dimethyl glutarate (CAS RN 1119-40-0), — 10 % or more but not more than 30 % of dimethyl adipate (CAS RN 627-93-0), and — not more than 35 % of dimethyl succinate (CAS RN 106-65-0)	1.1.-31.12.	10 000 tonnes	0 %
09.2542	ex 3824 99 92	97	Mixture containing bis[3-(triethoxysilyl)propyl]polysulfides (CAS RN 211519-85-6) with a purity by weight of 84 % or more	1.1.-31.12.	2 000 tonnes	0 %
09.2907	ex 3824 99 93	67	Mixture of phytosterols, in the form of powder, containing by weight: — 75 % or more of sterols, — not more than 25 % of stanols, for use in the manufacture of stanols/sterols or stanol/sterol esters <sup>(1)</sup>	1.1.-31.12.	2 500 tonnes	0 %

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty rate
09.2568	ex 3824 99 96	91	Mixture, in pellet form, containing by weight: — 49 % or more but not more than 50 % of bis[3-(triethoxysilyl)propyl] polysulphides (CAS RN 211519-85-6), and — 50 % or more but not more than 51 % of carbon black (CAS RN 1333-86-4), of which 75 % by weight or more pass through a sieve with an aperture of 0,60 mm, but not more than 10 % pass through a sieve with an aperture of 0,25 mm (as determined by the ASTM D1511 method)	1.1.-31.12.	2 100 tonnes	0 %
09.2820	ex 3827 90 00	10	Mixtures containing by weight: — 60 % or more but not more than 90 % of 2-chloropropene (CAS RN 557-98-2), — 8 % or more but not more than 14 % of (Z)-1-chloropropene (CAS RN 16136-84-8), — 5 % or more but not more than 23 % of 2-chloropropane (CAS RN 75-29-6), — not more than 6 % of 3-chloropropene (CAS RN 107-05-1), and — not more than 1 % of ethyl chloride (CAS RN 75-00-3)	1.1.-31.12.	6 000 tonnes	0 %
09.2671	ex 3905 99 90	81	Poly(vinyl butyral)(CAS RN 63148-65-2): — containing by weight 17,5 % or more, but not more than 20 % of hydroxyl groups, and — with a median particle size (D50) of more than 0,6 mm	1.1.-31.12.	12 500 tonnes	0 %
09.2846	ex 3907 40 00	25	Polymer blend of polycarbonate and poly(methyl methacrylate) with a polycarbonate content of not less than 98,5 % by weight, in the form of pellets or granules, with a luminous transmittance of not less than 88,5 %, measured using a test sample with a thickness of 4 mm at a wavelength of $\lambda = 400$ nm (according to ISO 13468-2)	1.1.-31.12.	2 000 tonnes	0 %
(*)09.2585	ex 3907 61 00 ex 3907 69 00 ex 3907 99 80	20 20 70	Copolymer of poly(ethylene terephthalate) and cyclohexane dimethanol, containing more than 10 % by weight of cyclohexane dimethanol	1.1.-31.12.	60 000 tonnes	2 %

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty rate
09.2855	ex 3910 00 00	10	Liquid poly(methylhydrosiloxane) with terminal trimethylsilyl groups (CAS RN 63148-57-2) with a purity by weight of 99,9 % or more	1.1.-31.12.	1 000 tonnes	0 %
09.2931	ex 3911 90 11	10	Poly(oxy-1,4-phenylenesulphonyl-1,4-phenyleneoxy-1,4-phenyleneisopropylidene-1,4-phenylene) (CAS RN 25135-51-7 and CAS RN 25154-01-2), in one of the forms mentioned in note 6(b) to this chapter containing by weight not more than 20 % of additives	1.1.-31.12.	6 300 tonnes	0 %
09.2723	ex 3911 90 19	35	Poly(oxy-1,4-phenylenesulfonyl-1,4-phenyleneoxy-4,4'-biphenylene) (CAS RNs 25608-64-4 and 25839-81-0) containing by weight not more than 20 % of additives	1.1.-31.12.	5 000 tonnes	0 %
09.2816	ex 3912 11 00	20	Cellulose acetate flakes	1.1.-31.12.	75 000 tonnes	0 %
09.2561	ex 3912 39 85	60	Hypromellose (INN) (CAS RN 9004-65-3), for use in the manufacturing of food supplements or pharmaceuticals <sup>(1)</sup>	1.1.-31.12.	2 750 tonnes	0 %
09.2573	ex 3913 10 00	20	Sodium alginate extracted from brown seaweed (CAS RN 9005-38-3), with — a loss on drying of not more than 15 % by weight (4h at 105 °C), — a water-insoluble fraction of not more than 2 % by weight, calculated on the dry weight	1.1.-31.12.	2 000 tonnes	0 %
09.2641	ex 3913 90 00	87	Sodium hyaluronate, non sterile, with: — a weight average molecular weight (Mw) of not more than 900 000, — an endotoxin level of not more than 0,008 Endotoxin units (EU)/mg, — an ethanol content of not more than 1 % by weight, — an isopropanol content of not more than 0,5 % by weight	1.1.-31.12.	300 kilograms	0 %
09.2661	ex 3920 51 00	50	Sheets of polymethylmethacrylate conforming to standards: — EN 4364 (MIL-P-5425E) and DTD5592A, or — EN 4365 (MIL-P-8184) and DTD5592A	1.1.-31.12.	100 tonnes	0 %

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty rate
09.2645	ex 3921 14 00	20	Cellular block of regenerated cellulose, impregnated with water containing magnesium chloride and quaternary ammonium compounds, measuring 100 cm (± 10 cm) x 100 cm (± 10 cm) x 40 cm (± 5 cm)	1.1.-31.12.	1 700 tonnes	0 %
09.2572	ex 5205 26 00 ex 5205 27 00	10 10	Raw white single cotton yarn — of combed fibres, — with an average fibre length of 36,5 mm or more, — produced through the compact ring spinning process with pneumatic compression, — with a tear strength of 26,5 cN/tex or more (according to ISO 2062:2009, at a speed of 5 000 mm/min)	1.1.-31.12.	50 000 tonnes	0 %
09.2848	ex 5505 10 10	10	Waste of synthetic fibres (including noils, yarn waste, and garnetted stock) of nylon or other polyamides (PA6 and PA66)	1.1.-31.12.	10 000 tonnes	0 %
09.2721	ex 5906 99 90	20	Woven and laminated rubberised textile fabric with the following characteristics: — with three layers, — one outer layer consists of acrylic fabric, — the other outer layer consists of polyester fabric, — the middle layer consists of chlorobutyl rubber, — the middle layer has a weight of 452 g/m <sup>2</sup> or more but not more than 569 g/m <sup>2</sup> , — the textile fabric has a total weight of 952 g/m <sup>2</sup> or more but not more than 1 159 g/m <sup>2</sup> , and — the textile fabric has a total thickness of 0,8 mm or more but not more than 4 mm, used for the manufacture of the retractable roof of motor vehicles (!)	1.1.-31.12.	375 000 square meters	0 %
09.2628	ex 7019 66 00	10	Glass web woven from glass fibre coated in plastic, of a weight of 120 g/m <sup>2</sup> (± 10 g/m <sup>2</sup> ), of a type used in rolling insect screens with fixed frames	1.1.-31.12.	3 000 000 square meters	0 %

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty rate
09.2652	ex 7410 11 00	50	Refined copper foil and strips, electrolytically manufactured, with a thickness of 0,015 mm or more but not more than 0,150 mm, used for the manufacture of laminates for Printed Circuit Boards and of Printed Circuit Boards in the printed circuit board industry <sup>(1)</sup>	1.1.-31.12.	1 020 tonnes	0 %
09.2662	ex 7410 21 00	55	Plates: — consisting of at least one layer of fibreglass fabric impregnated with epoxide resin, — covered on one or both sides with copper foil with a thickness of not more than 0,15 mm, — with a dielectric constant (DK) of less than 5,4 at 1 MHz, as measured according to IPC-TM-650 2.5.5.2, — with a loss tangent of less than 0,035 at 1 MHz, as measured according to IPC-TM-650 2.5.5.2, — with a comparative tracking index (CTI) of 600 or more	1.1.-31.12.	108 000 square meters	0 %
09.2795	7601 20 30 7601 20 40		Slabs and billets of unwrought aluminium alloys	1.1.-31.12.	573 000 tonnes	4 %
09.2835	ex 7604 29 10	30	Aluminium alloy rods with a diameter of 300,1 mm or more, but not more than 533,4 mm	1.1.-31.12.	1 000 tonnes	0 %
09.2736	ex 7607 11 90 ex 7607 11 90 ex 7607 11 90 ex 7607 11 90	75 77 78 79	Aluminium and magnesium alloy strip or foil: — of an alloy conforming to standards 5182-H19 or 5052-H19, — in rolls with an outside diameter of minimum 1 250 mm but not more than 1 350 mm, — of a thickness (tolerance - 0,006 mm) of 0,15 mm, 0,16 mm, 0,18 mm or 0,20 mm, — of a width (tolerance $\pm$ 0,3 mm) of 12,5 mm, 15,0 mm, 16,0 mm, 25,0 mm, 35,0 mm, 50,0 mm or 356 mm, — having a camber tolerance of not more than 0,4 mm/750 mm, — of a flatness measurement: I-unit $\pm$ 4,	1.1.-31.12.	600 tonnes	0 %

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty rate
			<ul style="list-style-type: none"> <li>— having a tensile strength of more than (5182-H19) 365 MPa or (5052-H19) 320 MPa, and</li> <li>— of an elongation A50 of more than (5182-H19) 3 % or (5052-H19) 2,5 %, for use in the manufacture of slats for blinds (!)</li> </ul>			
09.2722	8104 11 00		Unwrought magnesium, containing at least 99,8 % by weight of magnesium	1.1.-31.12.	120 000 tonnes	0 %
09.2840	ex 8104 30 00	20	Magnesium powder: <ul style="list-style-type: none"> <li>— of purity by weight of 98 % or more, but not more than 99,5 %, and</li> <li>— with a particle size of 0,2 mm or more but not more than 0,8 mm</li> </ul>	1.1.-31.12.	2 000 tonnes	0 %
09.2629	ex 8302 49 00	91	Aluminium telescopic handle for use in the manufacture of luggage (!)	1.1.-31.12.	1 500 000 pieces	0 %
09.2029	ex 8409 91 00	15	Cylinder head blank for a four cylinder engine with 10 cores, made of aluminium alloy EN AC-45500, with: <ul style="list-style-type: none"> <li>— no other components,</li> <li>— a hardness of 52 HRB or more,</li> <li>— casting defects size of not more than 0,4 mm and not more than 10 defects per cm<sup>2</sup>,</li> <li>— a dendrite arm space in combustion chamber of not more than 25 µm,</li> <li>— a double deck water jacket design,</li> <li>— a weight of 14 kg or more but not more than 19 kg,</li> <li>— a length of 506 mm or more but not more than 510 mm,</li> <li>— a height of 282 mm or more but not more than 286 mm and</li> <li>— a width of 143,7 mm or more but not more than 144,3 mm</li> </ul>	1.7.-31.12.	100 000 pieces	0 %

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty rate
09.2031	ex 8411 99 00	45	Turbine ring segments, guide and rotor blades as parts of a stationary gas turbine for power generation or as a mechanical drive <ul style="list-style-type: none"> <li>— made of nickel-based superalloys,</li> <li>— for an operating temperature of more than 600 K but not more than 1 600 K,</li> <li>— with a length of not more than 500 mm,</li> <li>— with a width of not more than 900 mm,</li> <li>— with a height of not more than 1 300 mm</li> </ul>	1.7.-31.12.	615 000 kilograms	0 %
09.2720	ex 8413 91 00	50	Pump head for two cylinder high pressure pump made of forged steel, with: <ul style="list-style-type: none"> <li>— milled threaded fittings with a diameter of 10 mm or more but not more than 36,8 mm, and</li> <li>— drilled fuel channels with a diameter of 3,5 mm or more but not more than 10 mm, of a kind used in diesel injection systems</li> </ul>	1.1.-31.12.	65 000 pieces	0 %
09.2569	ex 8414 90 00	80	Turbocharger wheel housing of cast aluminium alloy or cast iron: <ul style="list-style-type: none"> <li>— with a heat resistance up to 400 °C,</li> <li>— with a hole of 30 mm or more but not more than 300 mm for the insertion of the compressor wheel,</li> </ul> for use in the automotive industry <sup>(1)</sup>	1.1.-31.12.	4 000 000 pieces	0 %
09.2570	ex 8482 91 90	10	Rollers with a logarithmic profile and a diameter of 25 mm or more but not more than 70 mm or balls with a diameter of 30 mm but not more than 100 mm, <ul style="list-style-type: none"> <li>— made of 100Cr6 steel or 100CrMnSi6-4 steel (ISO 3290),</li> <li>— with a deviation of 0,5 mm or less as determined with the FBHmethod</li> </ul> for use in wind turbine industry <sup>(1)</sup>	1.1.-31.12.	600 000 pieces	0 %

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty rate
09.2562	ex 8482 99 00	30	Brass cages with the following characteristics: — continuously or centrifugally cast, — turned, — containing by weight 35 % or more, but not more than 38 % of zinc, — containing by weight 0,75 % or more, but not more than 1,25 % of lead, — containing by weight 1,0 % or more, but not more than 1,4 % of aluminium, and — with a tensile strength of 415 Pa or more, of a kind used for the manufacture of ball bearings	1.1.-31.12.	550 000 pieces	0 %
09.2557	ex 8482 99 00	60	Inner or outer rings made of steel, not hardened or not grinded, outer ring with internal raceway(s), inner ring with external raceway(s), with external diameters of: — 14 mm or more but not more than 77 mm for the inner ring, — 26 mm or more but not more than 101 mm for the outer ring, for use in the manufacture of bearings <sup>(1)</sup>	1.1.-31.12.	2 000 pieces	0 %
09.2552	ex 8482 99 00	70	Male and female parts of cages, — made of flat-rolled steel, — with a diameter of 14,5 mm or more but not more than 420 mm, — the male part including rivets, — the female part including holes, used for manufacturing of deep groove ball bearings <sup>(1)</sup>	1.1.-31.12.	1 221 tonnes	0 %

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty rate
09.2553	ex 8482 99 00	80	Punched cages of various diameters, — made of flat rolled steel, — with tensile strength of 270 MPa or more, for the production of tapered roller bearings <sup>(1)</sup>	1.1.-31.12.	8 000 000 pieces	0 %
09.2560	ex 8501 31 00	85	Power transmission device for controlling the output of exhaust gas turbochargers, consisting of: — a DC motor of an output not exceeding 600 W, — for usage with a supply voltage of 8 V or more but no more than 48 V, — with motor connection (plug-in connection), — whether or not with position sensor, — whether or not with integrated control and power electronics, — whether or not with spring mechanism for resetting the lever, — built in a housing with reduction gear and lever attached to the motor drive shaft, or — built in a housing with threads integrated into the rotor of the motor for linear movement of the integrated control rod	1.1.-31.12.	650 000 pieces	0 %
09.2559	ex 8501 40 20 ex 8501 40 80	70 70	Electric AC motor, single-phase, whether or not with commutator — with a nominal output of 180 W or more, — with an input power of 150 W or more but not more than 2 700 W, — with an external diameter of more than 44,8 but not more than 135,2 mm, — with a rated speed of more than 10 000 rpm but not more than 50 000 rpm, — whether or not equipped with air-inducting ventilator, — whether or not with mechanical device (pinion, screws, gear connection etc.) on the shaft, for use in the manufacture of domestic appliances <sup>(1)</sup>	1.1.-31.12.	2 000 000 pieces	0 %

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty rate
09.2554	ex 8505 11 10 ex 8505 11 90 ex 8505 19 90	74 74 74	Articles in shape of flat bars, arched bars, quarter sleeves or trapezoid whether or not arched, rounded corners or oblique sides made of ferrite, or cobalt, or samarium or other rare-earth metals, or their alloy, — whether or not overmolded with polymers, — whether or not coated or passivated with a surface treatment, with: — a length of 5 mm or more, but not more than 60 mm, — a width of 5 mm or more, but not more than 40 mm, — a thickness of 3 mm or more, but not more than 15 mm, intended to become permanent magnets after magnetisation	1.1.-31.12.	460 tonnes	0 %
09.2555	ex 8505 11 10	76	Articles of an alloy of neodymium, or an alloy of samarium, — whether or not coated or passivated with a surface treatment, — whether or not covered with zinc, — in the shape of rectangles, with: — a length of 13,8 mm or more but not more than 45,2 mm, — a width of 7,8 mm or more but not more than 25,2 mm, — a height of 1,3 mm or more but not more than 4,7 mm, intended to become permanent magnets after magnetisation	1.1.-31.12.	350 tonnes	0 %
09.2556	ex 8505 11 10	77	Article of an alloy of neodymium, in the form of arched rectangles, whether or not coated or passivated with a surface treatment, with: — a width of 9,1 mm or more but not more than 10,5 mm, — a length of 20 mm or more but not more than 30,1 mm, intended to become permanent magnets after magnetization	1.1.-31.12.	50 tonnes	0 %

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty rate
09.2574	ex 8537 10 91	73	Multifunctional device (instrument cluster) with: <ul style="list-style-type: none"> <li>— curved TFT LCD display (radius 750 mm) with touch-sensitive surfaces,</li> <li>— microprocessors and memory chips,</li> <li>— acoustic module and loudspeaker,</li> <li>— connections for CAN, 3 x LIN bus, LVDS and Ethernet,</li> <li>— for operating various functions (e.g. chassis, lighting) and</li> <li>— for situation-related display of vehicle and navigation data (e.g. speed, odometer, charge level of the drive battery),</li> </ul> for use in the manufacture of passenger cars powered solely by an electric motor covered by HS subheading 8703 80 <sup>(1)</sup>	1.1.-31.12.	66 900 pieces	0 %
09.2558	ex 8543 70 90	87	An electronic sound generator, creating an analog signal for a device producing the sound of an engine, containing: <ul style="list-style-type: none"> <li>— a printed circuit board with a microprocessor and a sound amplifier,</li> <li>— a connector,</li> <li>— a plastic housing,</li> <li>— with or without a metal holder,</li> </ul> for use in the manufacture of goods of Chapter 87 <sup>(1)</sup>	1.1.-31.12.	30 000 pieces	0 %
09.2910	ex 8708 99 97	75	Aluminium alloy support bracket, with mounting holes, whether or not with fixation nuts, for indirect connection of the gearbox to the car body for use in the manufacture of goods of Chapter 87 <sup>(1)</sup>	1.1.-31.12.	200 000 pieces	0 %
09.2668	ex 8714 91 10 ex 8714 91 10 ex 8714 91 10	21 31 75	Bicycle frame, constructed from carbon fibres and artificial resin, for use in the manufacture of bicycles (including electric bicycles) <sup>(1)</sup>	1.1.-31.12.	600 000 pieces	0 %

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty rate
09.2564	ex 8714 91 10	25	Frame, constructed from aluminium or aluminium and carbon fibres and artificial resin, for the use in the manufacture of bicycles (including electric bicycles) <sup>(1)</sup>	1.1.-31.12.	9 600 000 pieces	0 %
	ex 8714 91 10	35				
	ex 8714 91 10	77				
09.2579	ex 9029 20 31	40	Clustered instrument panel with: — stepping motors, — analog pointers and dials, — or without microprocessor control board, — or without LED indicators or LCD display, — showing at least: — speed, — engine revolutions, — engine temperature, — the fuel level, — communicating via CAN-BUS and/or K-LINE protocols, for use in the manufacture of goods of Chapter 87 <sup>(1)</sup>	1.1.-31.12.	160 000 pieces	0 %
	ex 9029 90 00	40				

<sup>(1)</sup> Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013.  
<sup>(2)</sup> However, the suspension of tariff duties does not apply where the processing is carried out by retail or catering undertakings.  
<sup>(\*)</sup> TARIC codes ex 3907 61 00 20 and ex 3907 69 00 20 shall apply from 1 July 2025.

TABLO

G.T.P.	Dipnot	Eşyanın Tanımı	Birim	Miktarı	Gümrük Vergisi %
2712.20.90	*	Parafin	Ton	10.000	0
2811.19.80.90.19	*	*Ağırlıkça %98,5 veya daha fazla saflıkta fosforöz asit (CAS RN 13598-36-2).	Ton	2.000	0
2914.19.90	*	*Minimum %99,5 saflıkta ve aşağıdaki özelliklerde asetilaseton (CAS RN 123-54-6): maksimum % 0,1 asetik asit içeren, maksimum % 0,1 su içeren, maksimum 15 APHA renk değerinde, kırınma indisi $1,450 \pm 0,002$ yoğunluğu: $0,970 - 0,975 \text{ g/cm}^3$ (20°C).	Ton	1.100	0
2915.21	*	*Ağırlıkça %99 veya daha fazla saflıkta asetik asit (CAS RN 64-19-7).	Ton	70.000	0
2915.32	*	Vinil Asetat.	Ton	107.000	0
2916.12.00.00.13	*	Butil Akriolat (CAS RN 141-32-2).	Ton	65.000	0
2926.10	*	*55. fasıl ve 68.15 GTP'li ürünlerin üretiminde kullanılan akrilonitril.	Ton	120.000	0
2931.90.00	*	*Tekstil apreleme malzemesinin hammaddesi olarak kullanılan ağırlıkça %99 veya daha fazla saflıkta oktametilsiklotetrasiloksan (CAS RN 556-67-2).	Ton	5.000	0
2932.20.90	*	*Epsilon-Kaprolakton.	Ton	800	0
3804.00	*	*Kuru ağırlığı hesaplandığında %55 veya daha fazla sodyum lügnosülfonat içeren sodyum lügnosülfonat sulu çözeltisi.	Ton	1.800	0
3806.10	*	*Yalnız doğal reçine ve doğal reçinelerden elde edilen reçine asitleri.	Ton	40.000	0
3815.19.90	*,a	Dizel üretiminde organik ve inorganik safsızlıklara karşı kullanılan, tek bileşenler veya set halinde ithal edilen, aşağıdaki müstahzarlardan en az birinden oluşan katalizör sistemi bileşenleri: - seramik malzeme (CAS RN 66402-68-4), - alüminyum oksit üzerinde desteklenen molibden oksit ve nikel oksit, - alüminyum oksit üzerinde desteklenen molibden oksit, nikel oksit, alüminyum fosfat, silika, molibden, su ve organik katkı maddesi, - alüminyum oksit üzerinde desteklenen molibden oksit, nikel oksit, alüminyum fosfat, zayıf organik asit, metal oksit ve su, - alüminyum oksit üzerinde desteklenen molibden oksit, alüminyum fosfat, zayıf organik asit, su ve kobalt oksit.	Ton	800	0
3815.90.90	*	*Yalnız titanyum oksit ve tungsten trioksit içeren katalizör.	Ton	450	0

G.T.P.	Dipnot	Eşyanın Tanımı	Birim	Miktarı	Gümrük Vergisi %
3903.30	*	*Çamaşır makinesi, bulaşık makinesi ve buzdolabı iç ve dış aksam parçalarının üretiminde kullanılan kendinden renkli, UV dayanımı ve antistatik özelliklere sahip aşağıdakileri içeren; - Gerilme katsayısı 2250 MPa (Megapascal) veya daha fazla fakat 2270 MPa dan az olan (ISO 527 metoduna göre belirlenmiş), - Kopmada gerilme dayanımı % 25 (ISO 527 ye göre belirlenmiş), - 220 °C 'de 10 kg' mının erime akış hızı 10g/10dk veya daha fazla fakat 21 g/10dk' dan az olan (ISO 1133 e göre belirlenmiş), - Renk değeri ISO 11664-4 test metoduna göre belirlenmiş; • "L" değeri 92,80 eşit veya daha fazla ve 94'e eşit veya daha az olmalı, • "a" değeri -006'ya eşit veya daha fazla ve -3,02'ye eşit veya daha az olmalı, • "b" değeri -0,62'ye eşit veya daha fazla ve -1,82'ye eşit veya daha az olmalıdır akrilonitril butadien stiren kopolimeri.	Ton	4.000	0
3907.29.20	*	*(NJ 406) Tolüen diamini ve propilen oksit reaksiyonu sonucu elde edilen polietilen poliyol (OH 380-415 mg KOH/g, Vizkosite: 15000-20000 mPas).	Ton	2.200	0
3907.29.20	*	*(NJ 4502) Sütkroz-gliserol ve propilen oksit reaksiyonu sonucu elde edilen polietilen poliyol (OH 430-470, Vizkosite:15000-20000 mPas).	Ton	14.500	0
7606.12.99	*,a	NADCAP ve AS9100 sertifikalı, 7040 serisi alüminyum alaşımlı levha: -193.746 mm2'den yüksek katı dikdörtgen kesit alanı için 130mm veya daha fazla fakat 149mm'den fazla olmayan bir kalınlığa veya -166.203 mm2'den yüksek katı dikdörtgen kesit alanı için 150 mm veya daha fazla ancak 180 mm'den fazla olmayan bir kalınlığa sahip havacılık endüstrisi ürünlerinin imalinde kullanılmaya mahsus .	Ton	30	0
8414.30.81.90.00	*,a	*Rotatif (rotary) tip kompresör, soğutma kapasitesi 2 kW ile 8kW arasında olan tek veya üç fazlı motora sahip, R32 veya R410 tip refrijeran sıvı kullanan, klimaların üretimine mahsus olan.	Adet	2.000.000	0
8504.31.80	*,a	Elektrik transformatörü: - güç taşıma kapasitesi 1 kVA'yı geçmeyen , - bir ferrit nüveye sahip, - fiş veya kablosu olmayan, - sıvı izolasyonu olmayan, çamaşır makineleri, çamaşır kurutma makineleri, bulaşık makineleri, fırınlar, klimalar, buzdolapları ve termosifonların imalatında güç ve kontrol kartları için dahili olarak kullanılmaya mahsus.	Adet	13.000.000	0

G.T.P.	Dipnot	Eşyanın Tanımı	Birim	Miktarı	Gümrük Vergisi %
8504.31.80	*,a	Elektrik transformatörü: • güç taşıma kapasitesi 1 kVA'yı geçmeyen, • fiş veya kablosu olmayan, • sıvı izolasyonu olmayan, TV'lerin, VS'lerin (görsel çözümler, monitör, akıllı tahta) ve set üstü kutuların imalatında dahili olarak kullanılmaya mahsus.	Adet	10.000.000	0
8507.50.00	*,a	*Nikel—metal hidrit (NiMh) akümülatörler: -voltajı 150 V veya daha fazla olan ancak, 300 V'u geçmeyen, -uzunluğu 220 mm veya daha fazla olan ancak, 500 mm'yi geçmeyen, -genişliği 500 mm veya daha fazla olan ancak, 1125 mm'yi geçmeyen, -yüksekliği 100 mm veya daha fazla olan ancak, 235 mm'yi geçmeyen, 87. fasılda yer alan motorlu taşıtların imalinde kullanılmaya mahsus.	Adet	185.000	0
8507.60.00 veya 8507.80.00	*,a	*Yeniden şarj edilebilir lityum iyon polimer piller (batarya): -nominal kapasitesi 1 060 mAh olan, -nominal gerilimi 7,4 V (ortalama gerilimi 0,2 C'de deşarj) olan, -8,4 V'luk ( $\pm 0,05$ ) voltajı olan, -uzunluğu 86,4 mm ( $\pm 0,1$ ) olan, -genişliği 45 mm ( $\pm 0,1$ ) olan, -yüksekliği 11 mm ( $\pm 0,1$ ) olan, yazarkasaların imalinde kullanılmaya mahsus.	Adet	100.000	0
8507.60.00	*,a	*Lityum-iyon akümülatör: -Kalınlığı 6 mm fazla olmayan, -Genişliği 100 mm fazla olmayan, -Uzunluğu 150,15 mm fazla olmayan, - Nominal kapasitesi 1.000 mAh veya daha fazla olan ancak, 10.000 mAh'den fazla olmayan, -Ağırlığı 150 gr'dan fazla olmayan, 8517.13.00 alt başlığında yer alan ürünlerin imalinde kullanılmaya mahsus.	Adet	11.000.000	0
8507.60.00	*,a	*Lityum İyonlu (Li-Ion) Akümülatörler: -Voltajı 150 V veya daha fazla olan ancak, 300 V'u geçmeyen, -Uzunluğu 290 mm veya daha fazla olan ancak 490 mm'yi geçmeyen, -Genişliği 670 mm veya daha fazla olan ancak 1120 mm'yi geçmeyen, -Yüksekliği 140 mm veya daha fazla olan ancak 230 mm'yi geçmeyen, 87. fasılda yer alan motorlu taşıtların imalinde kullanılmaya mahsus.	Adet	138.000	0

G.T.P.	Dipnot	Eşyanın Tanımı	Birim	Miktarı	Gümrük Vergisi %
8529.90.93.00.00 veya 8539.51.00.00.00 9405.41.31.00.00 9405.42.31.00.00 9405.49.40.00.00	*,a	*Yalnız LED Diyotlu Baskılı Devre Kartı; prizmalar/lensler ile donatılmış olsun ya da olmasın, bağlayıcı(lar) ile donatılmış olsun ya da olmasın, 85.28 başlığındaki ürünlerin arka ışık ünitelerinin imaline mahsus.	Adet	40.000.000	0
9503.00.75	*,a	*Aşağıdaki özelliklere sahip kare veya dikdörtgen şeklinde baskı devre kartları: - plastikten yapılmış bir gövde, - ön tarafında voltaj kontrolü sağlayan bir potansiyometre, - komutları iletmek için devre kartlarına bağlı renkli kablolar oyuncakların (arabaların) imalinde kullanılmaya mahsus.	Adet	5.000.000	0
9503.00.95	*,a	*Aşağıdaki özelliklere sahip ses mekanizması: - plastikten yapılmış bir gövde(genellikle ten renginde), - gövdenin üst kısmında hoparlör delikleri, - gövdenin altında bir yalıtım şeridi, - yalıtım şeridi çıkarıldıktan sonra gövdenin üst kısmına bastırılarak çalışan bir mekanizma, - düğmeye basıldığında çalan önceden yüklenmiş sesler oyuncakların (oyuncak bebeklerin) imalinde kullanılmaya mahsus.	Adet	3.000.000	0

\* : Bu GTP'lerde sadece eşya tanımı sütununda özellikleri belirtilen ürünler için vergi oranı düşürülmüştür.

(a) : Bu GTP'lerde sadece eşya tanımı sütununda belirtilen amaçlar için vergi oranı düşürülmüştür; bu eşya gümrük mevzuatının nihai kullanıma ilişkin hükümlerine tabidir.

**TABLO**

<b>G.T.P.</b>	<b>Dipnot</b>	<b>Eşyanın Tanımı</b>	<b>Birim</b>	<b>Miktarı</b>	<b>Gümrük Vergisi %</b>
2921.45.00	*	2-aminonaftalin-1,5-disülfonik asit (CAS RN 117-62-4) veya bunun sodyum tuzlarından (CAS RN 19532-03-7 veya 62203-79-6) biri.	Kg	60.000	0
2921.45.00	*	7-aminonaftalin-1,3,6-trisülfonik asit (CAS RN 118-03-6).	Kg	75.000	0
2921.51.19	*	2,4-diaminobenzensülfonik asit (CAS RN 88-63-1).	Kg	30.000	0
2924.21.00	*	(3-aminofenil) üre hidroklorür (CAS RN 59690-88-9).	Kg	55.000	0
2930.90.95	*	2-[(4-amino-3-metoksifenil)sülfonil]etil hidrojen sülfat (CAS RN 26672-22-0).	Kg	25.000	0
9607.20.10	*, a	Fermuar imalinde kullanıma mahsus, adi metalden fermuar sürgüleri, monte edilmiş fermuar dişlerine sahip dar bant, pinler/kutucuklar ve diğer fermuar aksamı.	Kg	2.500.000	0

\* : Bu GTP'lerde sadece eşya tanımı sütununda özellikleri belirtilen ürünler için vergi oranı düşürülmüştür.

(a) : Bu GTP'lerde sadece eşya tanımı sütununda belirtilen amaçlar için vergi oranı düşürülmüştür; bu eşya gümrük mevzuatının nihai kullanıma ilişkin hükümlerine tabidir.